



**CARTFT.COM**  
Shop for mobile  
PC- and GPS-Solutions

**FBox-PC-Mini-PCI (1.2Ghz, 1024MB RAM, Mini-PCI Slot) [FANLESS] (available on 18.12.2008)**

[<http://www.cartft.com/catalog/il/1000>]



999.00 EUR

incl. 19% VAT, plus shipping

- **Fanless !**
- **1GB RAM !**
- **1.2 Ghz !**
- **Mini-PCI slot !**



Fanless PC-Barebone. For a full-featured PC you only need to add one 2.5" PATA harddrive.

Because of its size (170 x 123 x 56 mm !) the system is perfect for these applications :

- POS
- Digital Signage
- Kiosk

Or use as attractive office-computer or server.

|                |  |
|----------------|--|
| CPU            | VIA Eden Esther 1.2GHz processor               |
| BIOS           | AMI BIOS                                       |
| System Chipset | VIA CX700M                                     |
| I/O Chip       | VT1211   |
| System Memory  | Onboard 1024MB DDR2                            |
| MIO            | 1xEIDE(UltraDMA 133),1x PS/2 K/B,1x P/S2 Mouse |
|                | 1x Mini-PCI Slot (internal)                    |
| PRT            | 1x Printer port                                |
| RS232          | 2x RS-232 port                                 |

|                                     |   |
|-------------------------------------|---|
| USB                                 | 2 X USB 2.0 Ports (one at front)  |
| Output                              | VGA   |
| Display Chipset                     | Integrated VIA UniChrome Pro II,2D/3D Graphics with MPEG4 and WMV9 decoding accelerator |
| Display Memory                      | Up to 128MB share system memory   |
| Display Resolution                  | Up to 1920 x 1440   |
| Audio AC97 2.2(Codec)               | VIA Vinyl VT1708  |
| Audio Interface                     | Line Out, Mic In  |
| Ethernet Chipset                    | Realtek RTL8100B 10/100 Base-T Ethernet   |
| Ethernet Remote Boot ROM            | built-in boot ROM function (PXE Supported)  |
| 2.5" Hard Disk installation support | YES   |
| Power Requirement                   | +5V@4A  |
| Operating Temp                      | 0 ~ 60°C ( 32-140 °F)   |
| Operating Humidity                  | 0% - 90% relative humidity, non-condensing  |
| Size (W x H x D)                    | 170 x 123 x 56 mm   |
| Weight                              | 970g  |
| Certification                       | CE,FCC  |