



339.00 EUR

incl. 19% VAT, plus shipping

- High brightness !
- Slim design !
- Auto-PowerOn !
- LED-Backlight !

Support: [800x480 Driver \(Windows 7\)](#)

New : LED-Backlight-Technology, with optimized color saturation enabling particular high and shining display. The scale of displayable color nuances is increased by 45% because of the new technology. Conventional LCDs are based on CCFL backlight, which can display approx. 72% of the standard color scale of NTSC (National Television Systems Committee). With LED-Backlight-Technology 104% of the NTSC-color scale can be displayed. This results in displaying in a highly realistic manner.

With maximum depth of 29mm the new slim CTF800-L will convince you. Its the ideal display- and control unit for your Laptop, CarPC or HTPC. With help of the touchscreen functionality, the PC can be controlled comfortable with your fingers. The brilliant VGA-display enables a maximum readability and sharpness.

The device has integrated Stereo-speakers and an automatically switched rear camera input. An AC-Home adapter and a cigarette lighter adapter is included with the package, as well as an IR-remote control unit and the extralong (2,5 meters) All-In-One connector cable.

Driver-CD included, compatible with :

- Windows 95/98/ME/NT4/2000/XP/7/8/8.1/10
- XP Tablet PC Edition
- Windows CE 2.12, 3.0, .net
- Linux RedHat,Mandrake,..
- Macintosh OS 9.x, 10.x
- DOS,..

Spezifications

| | |
|------------------------------|--|
| <i>Screen size</i> | 8" digital |
| <i>Aspect Ratio</i> | 16:9 wide TFT screen |
| <i>Dot Resolution</i> | 2400x480= 1,152,000 dots |
| <i>Physical Resolution</i> | 800x480 (1024x600 possible on request) |
| <i>Supported Resolutions</i> | 640x480-1920x1200 (also eg. 1366x768) |
| <i>Color configuration</i> | RGB stripe |

| | |
|------------------------------|--|
| <i>Power input</i> | DC 12V (12/24V available for project customers) |
| <i>Power consumption</i> | max. 9W |
| <i>Video system</i> | 3x Video inputs (PAL/NTSC) 1x VGA input |
| <i>Dimensions</i> | Display Case : 220x135x29 mm Display : 174 x 105 mm Headrest shroud : 238x153x30 mm |
| <i>Video input signal</i> | 1.0Vp-p, composite video |
| <i>Contrast</i> | 300:1 |
| <i>Brightness</i> | 500 cd/m ² |
| <i>Vibration</i> | IEC68-2-6 |
| <i>Operating Temperature</i> | -30° to 85°C |
| <i>Features</i> | Full function OSD control (english) Built-in Stereo-speakers Auto Power On/Off Autodimmer Automatic switching to rear camera (by a 12V cable) LED backlight |
| <i>What is included ?</i> | - 8" VGA Touchscreen TFT with Video/Audio-support - Infrared Remote Control - Car dash mounting bracket - Headrest shroud - Touchscreen pencil - VGA/Video/Audio/Touchscreen/Power-cable (all-in-one !) 2,5 meters length - Power Adapter f. EU 230V - Cigarette Lighter Adapter - Touchscreen Driver-CD - Manual |

Displays with [True-800x480-Support](#) achieve a pixel accurate view at 800x480@70Hz

