



**CARTFT.COM**  
Shop for mobile  
PC- and GPS-Solutions

**FleetPC-6 Car-PC (Intel Atom D525 2x1.8Ghz, 2GB RAM, Autostart-Controller, 9-36V Automotive PSU, CAN-BUS) [FANLESS]**  
[<http://www.cartft.com/catalog/il/1399>]



619.00 EUR

incl. 19% VAT, plus shipping

- **Fanless !**
- **Auto Power On/Off !**
- **CAN-BUS 2.0B**
- **4x RS232 !**

**CARTFT.COM**

**Support:** [Manual \[EN\]](#) | [Specifications](#) | [CAN-BUS Controller](#) | [GPIO Test-Code](#) | [Drivers \(Windows\)](#) | [CAN-BUS Drivers](#)

This MiniPC was especially designed for fleet applications. The Car-PC can be connected directly to the car battery (12V/24V). Based on ignition plus, the PC will start and shutdown.

For a full PC you need in addition :

- 2.5" HDD/SSD or CompactFlash

The PC is completely fanless and is equipped with an Intel Atom D525 2x1.8GHz CPU and 2GB RAM.

#### **Available additional modules:**

The PC comes with 5x antenna-output and sx Mini-PCIe slots and 2x Mini-module-slots

We recommend these modules:

- [HSPA / UMTS / EDGE Mini-PCIe Modem + GPS Combi card \(Sierra Gobi2000\)](#)
- [Wireless LAN / Bluetooth Mini-PCI Express \[Qcom Combo\]](#)
- [GPS Mini-Module](#)
- [BT Mini-Module](#)

#### **Features :**

- Fanless
- Intel Atom D525 Dual Core CPU
- 1x CAN BUS 2.0A/2.0B
- 4x RS232
- 1x Gigabit LAN
- 1x DSUB-15 VGA
- Watchdog
- Prepared for GPS, WLAN, GSM/GPRS with ext. antennas
- 8bit GPIO (4 x DI / 4 x DO)
- Vibration/shock tested

Dimensions / Weight	280mm W x 181.5 D x 76.8mm H
CPU	Intel Atom D525 Dual Core 2x 1.8GHz
Chipset	Intel ICH8M
RAM	1x SO-DDR-3 RAM (up to 4GB) [1x 2GB RAM included]
Graphics	Intel GMA
Expansion	- 2x Mini-PCIe - 2x Mini-Module
OS Support	Windows XP Home/Pro/Embedded, Windows 7, Linux
Vibration & Shock	IEC 60068-2-64, IEC 60068-2-27
Operating temperature	-20~50°C (with SSD or CF)
Certification	CE, FCC, E-Mark 13
I/O	- 1x Gigabit LAN (Realtek RTL8111D) - 4x RS232 (2x with RS-422/485) - 4x USB2.0 - GPIO port (4in, 4out) - Audio : Mic-In, SPK Out, Remote switch - 1x DSUB-15 VGA - 5x SMA Antenna hole (for eg. GPS, GSM/GPRS/3G, WLAN, Bluetooth) - SIM card slot - 2pin JST connector (CAN-BUS)
Drive bays	- 1x 2.5" SATA HDD/SSD drive bay - 1x External CF-card slot (Type I/II)
Power supply	9~32V DC PSU included - Power off Delay Time Setting by Software
Scope of supply	- FleetPC-6 PC with Intel Atom D525 (2x1.8Ghz), 2GB RAM, mounting