



194.00 EUR

incl. 19% VAT, plus shipping

Support:  [Specifications \[EN\]](#)

- INTEL® 945GSE + ICH7M Chipset
- Support INTEL® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)
- Build-in INTEL®GMA 950 Graphics Core
- Integrated LVDS support 18-bit TFT LCD
- Supports Dual Gigabit LAN
- Integrated ALC662 HD Audio CODEC with 6-CH
- Support Watch dog Technology
- Mini-ITX Form Factor(148mm x 102mm)

1. CPU

1. INTEL® Atom N270 CPU(45nm,512K Cache, 1.60 GHz, 533 MHz FSB)

1. Chipset

1. INTEL® 945GSE + ICH7M chipset
2. Build-in INTEL® GMA 950 Graphics Core(Share Memory Size: 128/224MB)
3. Front Side Bus 533MHz

1. Memory

1. 1 * SO-DIMM Sockets for un-buffered Single Channel DDR2 533/400 SDRAM up to 2 GB

1. Storage

1. 1 * Serial ATA2 3Gb/s connectors
2. 1 * Ultra DMA 133/100 IDE connector

1. Audio

1. Realtek ALC662 6-Channel HD Audio Codec

1. Ethernet LAN	1. 2 * Realtek RTL8111DL PCI-E Gigabit Ethernet LAN
1. LVDS	1. Onboard 18-bit dual channel LVDS connector
1. USB	1. Embedded 4 * USB 2.0 2.
1. Special Features	1. Intel Diamond Ville Platform 2. Support ACPI S3 3. Support CPU Smart FAN
1. Rear Panel I / O	1. 2 * USB 2.0 ports 2. 1 * PS KB connector 3. 2 * RJ-45 port 4. 3 * Audio I/O ports (Line-in, MIC and line-out) 5. 1 * 12V DC jack 6. 1 * DVI-I port
1. Internal I / O	1. 1* USB 2.0 headers for 2 USB 2.0 ports 2. NB / Chassis Fan connectors; 3. 1 * 20-pin ATX Power connector 4. 1 * 32-pin LVDS header & 1 * GPIO header & 1 * Parallel header 5. 2 * RS232 COM headers & 1 * RS422/485 header 6. 1 * Audio header & 1 * CF CARD header 7. 1 * Mini PCI-E connector
1. BIOS	1. Award 8MB DIP Flash ROM
1. Form Factor	1. Mini ITX Form Factor(148mm x 102mm)
1. Functional	1. ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
1. Certificate	1. CE, FCC, RoHS
1. Temperature	1. Operating within 0~60 centigrade 2. Storage within -20-85 centigrade

Product Accessories

- DVI-I to CRT Converter
- Manual
- CD

- 1x SATA cable
- SATA power cable