



199.00 EUR

incl. 19% VAT, plus shipping

**Support:**  [Specifications \[EN\]](#)

- INTEL® 945GSE + ICH7M Chipset
  - Support INTEL® ATOM™ N270 processor
  - Integrated INTEL® GMA950 graphic processor
  - Integrated LVDS support 18-bits dual channel TFT LCD
  - Realtek ALC662 HD Audio Codec with 2-Channel
  - Onboard Gigabit LAN
  - Support Watchdog timer, Support O.V.P
  - Support CPU smart FAN
  - Support ACPI S3 function
  - Compliance with EuP standard
  - 148 x 102mm 3.5" SBC Form Factor
- CPU
    - Support INTEL® ATOM™ N270 CPU (45nm, 512K cache, 1.60GHz, 533MHz FSB)
  - Chipset
    - INTEL® ATOM 945GSE + ICH7M chipset
  - Memory
    - 1 \* 240-pin SODIMM Socket for un-buffered single channel DDR2 533MHz SDRAM up to 2GB
  - Expansion Slots
    - 1 \* MINI PCI-E
  - Storage
    - **Embedded ICH7M chipset**
      - 1 \* Serial ATA2 3Gb/s connectors
      - 1 \* Ultra DMA 100 / 66 IDE header
  - Audio
    - Realtek ALC662 2-Channel HD Audio CODEC

- Ethernet LAN
- LVDS
- USB
- Special Features
- Rear Panel I / O
- Internal I / O
- BIOS
- Functional
- Form Factor
- Certificate
- Temperature
- Realtek RTL8111DL PCI-E Gigabit Ethernet LAN
- Onboard 18-bit dual channel LVDS connector
- Embedded 6\* USB 2.0/1.1
- Support ACPI S3
- Support CPU Smart FAN
- Support Watch Dog
- 4 \* USB 2.0/1.1 ports
- 1 \* RJ-45 port
- 2-CH Audio I/O ports ( Line-in and line-out )
- 1 \* DVI-I port
- 1 \* 12V DC-IN JACK
- 1 \* USB 2.0/1.1 headers for 2\* USB 2.0 ports
- 1 \* VGA header
- CPU / NB / Chassis Fan connectors;
- 1 \* 32-pin LVDS headers & 1 \* GPIO header & 1 \* CF card reader socket
- 2 \* COM header
- 1 \* AUDIO header& DIY switch x2 (reset & power button)
- Award 8MB SMT Flash ROM
- ATM, Automation, medical Equipment, Security, General Application, Transportation
- 3.5" SBC form factor (148mmx102mm)
- CE,FCC,RoHS,ERP
- Operating within 0~60 centigrade
- Storage within -20-85 centigrade

### **Product Accessories**

- DVI-I to CRT Converter
- Manual
- CD
- 1x SATA cable
- SATA power cable