



137.00 EUR

incl. 19% VAT, plus shipping



**Support:**  [Specifications \[EN\]](#)

- VIA VX800 Chipset
- Support VIA C7 1.5GHz(90nm,FSB 400MHz,1.5GHz) processor
- Integrated Chrome9 HC3 DX9 IGP
- Integrated LVDS support 24-bit TFT LCD
- Support 1 x 32-bit PCI slot
- Support 2 x Serial ATA 2 Devices
- Windows Vista Ready
- Onboard Gigabit LAN
- Support DC FAN
- COM2 Support RS422/485
- VIA VT1708B HD Audio Codec with 6-Channel
- 170 x 170mm Mini-ITX Form Factor
- Support Daughter board Expansion
- Support Watch dog Technology

1. CPU

1. Support VIA C7 1.5GHz(90nm,FSB 400MHz,1.5GHz) processor
2. Front Side Bus 400MHz

<b>1. Chipset</b>	<ol style="list-style-type: none"> <li>1. VIA VX800 Chipsets</li> <li>2. VIA Chrome9 HC3 IGP, 128Bit 3D engines( Share System Memory: 64/128/256MB)</li> </ol>
<b>1. Memory</b>	<ol style="list-style-type: none"> <li>1. 1 * 240-pin DIMM Sockets for un-buffered DDR2 667MHz SDRAM up to 2GB</li> </ol>
<b>1. Expansion Slots</b>	<ol style="list-style-type: none"> <li>1. 1 * 32-bit PCI slots</li> </ol>
<b>1. Power Management</b>	<ol style="list-style-type: none"> <li>1. ACPI S3/S4 Compliant ,supports VIA PowerSaver™ feature</li> </ol>
<b>1. Storage</b>	<ol style="list-style-type: none"> <li>1. 2 * Serial ATA2 3Gb/s connectors with RAID 0,1 functions</li> <li>2. 1 * Ultra DMA 133/100/66 IDE connector</li> </ol>
<b>1. Audio</b>	<ol style="list-style-type: none"> <li>1. VIA VT1708B HD Audio Codec with 6-Channel</li> </ol>
<b>1. Ethernet LAN</b>	<ol style="list-style-type: none"> <li>1. 1 * RTL8111C 10 / 100 / 1000 PCI LAN</li> </ol>
<b>1. USB</b>	<ol style="list-style-type: none"> <li>1. Embedded 6 * USB 2.0/1.1</li> </ol>
<b>1. LVDS</b>	<ol style="list-style-type: none"> <li>1. Onboard 24-bit dual channel LVDS connector</li> <li>2.</li> </ol>
<b>1. Rear Panel I / O</b>	<ol style="list-style-type: none"> <li>1. 2 * USB 2.0/1.1 ports</li> <li>2. 1 * PS/2 connector for Keyboard and Mouse</li> <li>3. 1 * RJ-45 ports</li> <li>4. 3 * Audio I/O ports ( Line-in, mic and line-out )</li> <li>5. 1 * VGA port</li> <li>6. 1 * DB-9 RS232 COM port</li> </ol>
<b>1. Internal I / O</b>	<ol style="list-style-type: none"> <li>1. 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports</li> <li>2. 1 * CPU Smart Fan Connector, 2 * Sys/Chassis Fan Connectors</li> <li>3. 3 * 9-Pin COM Port headers(COM2 Support RS422/RS485)</li> <li>4. 1 * IR header</li> <li>5. 1 * HDMI_SPDIF header</li> <li>6. 1 * LVDS header</li> </ol>
<b>1. BIOS</b>	<ol style="list-style-type: none"> <li>1. Award 4MB SPI Flash ROM</li> </ol>
<b>1. Form Factor</b>	<ol style="list-style-type: none"> <li>1. Mini-ITX Embedded Motherboard(170mmx170mm)</li> </ol>

1. Temperature

1. Operating within 0~60 centigrade

2. Storage within -20-85 centigrade

**Product Accessories**

- COM cable
- Manual
- CD
- 1x SATA cable
- I/O shield
- 1x IDE cable