



1019.00 EUR

incl. 19% VAT, plus shipping



**Support:**  [Specifications \[EN\]](#)

- AMD RS785 Chipset + SB750 Chipset
  - Support Socket AM2+ Quad core Opteron™ & Phenom™
  - Support HT3.0 Technology
  - Integrated ATI Radeon HD 4200(Support Microsoft DX 10.1)
  - Support 4 Serial ATA2 Devices with RAID 0,1,5,10
  - Support Dual Channel DDR2 800/667
  - Integrated ALC662 HD Audio CODEC with 6-CH
  - Support DVI-D/HDMI Output
  - Supports 10/100M LAN / Gigabit LAN
  - Compliance with EuP standard
  - Support CPU Smart FAN
  - Ready for Windows® 7™
  - ITX Form Factor(170mm x 170mm)
- |  |   |
|--|---|
| <ul style="list-style-type: none"><li>• CPU</li><li>• Chipset</li><li>• Memory</li></ul> | <ul style="list-style-type: none"><li>• Support AMD Socket AM2/AM2+</li><li>• AMD RS785 Chipset + SB750 Chipset</li><li>• 2 * SODIMM Sockets for un-buffered Dual Channel DDR2 800 SDRAM up to 4 GB</li></ul> |
|--|---|

- Expansion Slots
  - 1 \* 32-bit PCI slot
  - 1 \* MINI PCI-E Connector
- Storage
- Audio
- Ethernet LAN
- USB
- Special Features
- Rear Panel I / O
  - 6 \* USB 2.0/1.1 ports
  - 1 \* PS2 KB/MS port
  - 1 \* RJ-45 port & 2 \* e-SATA ports
  - 1 \* Audio I / O ports
  - 1 \* VGA port
  - 1 \* DVI-D port
  - 1 \* HDMI port
- Internal I / O
  - 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports
  - CPU / Chassis Fan connectors;
  - 1 \* 4-pin ATX 12V Power connector
  - 1 \* 20-pin ATX Power connector
  - 1 \* COM header
- Functional
  - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation
- Temperature
  - Operating within 0~50 centigrade
  - Storage within -20-85 centigrade
- BIOS
- Form Factor
  - 8MB SPI Flash ROM
  - Mini ITX Form Factor(17cmx17cm)

### **Embedded SB750 Chipset**

- 4 \* Serial ATA2 3Gb/s connectors
- Supports HDDs with RAID 0, 1,5,10 functions
- Realtek ALC662 6-Channel HD Audio CODEC
- Realtek RTL8111DL PCI-E LAN chip for 10/100M LAN / Gigabit LAN
- Embedded 10 \* USB 2.0/1.1
- Advanced Power Design that supports the latest Socket-AM2+ CPU
- “IMAGE IT!” System Backup Software and “ProMagicPLUS!” System Recovery System

- 6 \* USB 2.0/1.1 ports
- 1 \* PS2 KB/MS port
- 1 \* RJ-45 port & 2 \* e-SATA ports
- 1 \* Audio I / O ports
- 1 \* VGA port
- 1 \* DVI-D port
- 1 \* HDMI port
- 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports
- CPU / Chassis Fan connectors;
- 1 \* 4-pin ATX 12V Power connector
- 1 \* 20-pin ATX Power connector
- 1 \* COM header

- ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation

- Operating within 0~50 centigrade
- Storage within -20-85 centigrade

- 8MB SPI Flash ROM

- Mini ITX Form Factor(17cmx17cm)

### **Product Accessories**

- COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield