



114.95 EUR

incl. 19% VAT, plus shipping

Assemble the perfect small form factor system for all your computing demands with the flexible ZOTAC® H67-ITX WiFi mini-ITX platform. The ZOTAC® H67-ITX WiFi supports socket LGA1155 2nd generation Intel® Core™ family processors with turbocharged Intel® HD Graphics to let users select the perfect amount of processing power for their needs – whether it is dual or quad-core, with or without Intel® HyperThreading™ technology.

Demanding gamers can install a standard PCI Express x16 ZOTAC® graphics card in the H67-ITX WiFi to form a perfect miniature gaming PC that delivers big system power in a miniature form factor. A mix of seven total SATA 6.0 Gb/s, SATA 3.0 Gb/s and eSATA ports with RAID 0, 1, 5 and 10 support on the ZOTAC® H67-ITX WiFi enable users to maximize storage connectivity and complete the ultimate home theatre PC or home file server.

Product Name

Product Name ZOTAC H67-ITX WiFi

Model

Model H67ITX-C-E

Chipset

Manufacturer Intel
 Chipset H67 Express (B3)
 GPU Intel® HD Graphics ready

CPU Compatibility

Name 2nd Generation Intel® Core™ i3
 i5 & i7 Intel® HD Graphics
 2000/3000 ready
 Socket LGA1155
 Bus N/A

Memory

Memory Type DDR3
 Memory Speed 1066/1333 MHz
 Slots 2 x 240-pin DIMM

	Capacity	Up to 16GB
CPU and Memory Compatibility List	CPU and Memory Compatibility List	see above
3D API	DirectX	DirectX® 10.1
	OpenGL	OpenGL® 2.1
Expansion	Slots	1 x PCI Express x16
Networking	Ethernet	10/100/1000Mbps
	WiFi	802.11n/g/b (300Mb/s)
Audio	AN/Alog	8-ch HD
	Digital	Optical S/PDIF and HDMI outputs
Ports	DVI	1 (HDCP)
	HDMI	1 (1080p w/8-ch audio)
	Display Port	1
	VGA	1 (w/Adapter)
	SATA	2 (SATA 6.0 Gb/s) 4 SATA 3.0 Gb/s (w/RAID 0 / 1 / 0+1 / 5)
	eSATA	1 (SATA 3.0 Gb/s)
	PATA	N/A
	PS/2	1
	Serial Port	N/A
	USB Ports	8 x USB 2.0 (4 on back panel / 4 via pin header) 4 x USB 3.0 (2 onback panel / 2 via pin header) 8 USB 2.0 ports (4 on back panel / 4 via header)
	FireWire Ports	N/A
Cooler	Cooler	Passive (no fan)
Form Factor	Form Factor	mini-ITX
OS Compatibility	Windows	Windows® Vista / 7 Premum ready
General	SLI Supported	No
	Maximum Resolution	2048 x 1536
Other	Wake-On Support	Wake-on USB Wake-on-LAN
	Overclocking features	No

Packaging

Package Contents	4 x SATA cables 1 x 4-pin CPU power extension cable 1 x DVI-to-VGA adapter 1 x I/O back plate 2 x WiFi antennas 1 x USB 3.0 header (full-size bracket) 1 x USB 3.0 low-profile bracket
Graphics Output	1 DVI / 1 HDMI / 1VGA / 1 DP