



89.00 EUR

incl. 19% VAT, plus shipping

- INTEL® H61 Express Chipset
 - Support 2nd generation Intel Core processor(i3/i5/i7) family
 - Multi-monitor support with Windows * 7
 - Support PCI-Express 2.0
 - Support USB 3.0
 - Support Dual Channel DDR3 1333/1066
 - Integrated HD Audio CODEC with 6.0 CH
 - Support Gigabit LAN
 - 3+1+1 Phase CPU Power Support
 - Ready for Windows® 7™
 - ITX Form Factor(170mm X 170mm)
- **CPU**
 - **INTEL® LGA1155 Socket**
 - Support 2nd generation Intel Core processor(i3/i5/i7) family
 - Support Intel® Pentium® processor, and Intel® Celeron® processor.
 - Support Intel® Turbo Boost Technology 2.0
 - 3+1+1 Phase CPU Power Support
 - **INTEL® H61 Express Chipset**
 - Dual Channel DDR3 memory technology
 - 2 x DDR3 DIMM slots
 - Support DDR3 1333/1066 un-buffered memory
 - Max. capacity of system memory up to: 8GB
 - 1x PCI Express 2.0 x16(By 16) slot
- **Chipset**
 - **Memory**
 - **Expansion Slots**

- **Storage**

- **Audio**

- **Ethernet LAN**

- **USB**

- **Back Panel I / O**

- **Internal I / O**

- **BIOS**

- **Form Factor**

Embedded INTEL H61 Chipset:

- 4 x Serial ATA2 3Gb/s connectors
- VIA VT1705 Audio CODEC
- 5.1 CH HD Audio with Content Protection
- RTL8111E Chip
- PCI-Ex1 Gigabit LAN 10/100/1000 Mb/s
- Support PXE

INTEL H61 Chipset:

- 6 x USB 2.0 ports (4 distribute in back panel, 2 distribute in mid-board)
- 2 x USB 3.0 ports by ASMedia ASM1042 (2 distribute in back panel)
- 4 x USB 2.0/1.1 ports
- 2 x USB 3.0 ports
- 1 x PS/2 Keyboard / Mouse
- 1 x VGA Port
- 1 x DVI-D Port
- 1 x HDMI Port
- 1 x RJ-45 Port
- 3 x Audio jacks (Line In/Line Out/Microphone)
- 1 x USB 2.0/1.1 header for 2 USB 2.0/1.1 ports
- CPU / Chassis Fan connectors
- 1 x 4-pin ATX 12V Power connector
- 1 x 24-pin ATX Power connector
- 1 x HDMI_SPDIF header
- 1 x Front panel audio header
- 32 MB DIP Flash ROM
- ITX form Factor:170x170 mm