



174.00 EUR

incl. 19% VAT, plus shipping

Support:  [Specifications \[EN\]](#)

- Intel® H61 Express Chipset
- Supports Intel LGA 1155 Socket Core™ i3, i5, i7 & Pentium Processors
- 2 * Dual Channel DDR3-1333/1066 up to 16GB
- Realtek RT8111EVL Gigabit LAN
- PCI Express x16 Slot
- 4-port SATAII 3Gb/s
- DVI-D, and VGA Video Outputs
- Built-in Watchdog Timer Technology
- Mini-ITX Form Factor (170mm x 170mm)

• **CPU**

INTEL® LGA 1155 Socket Core i7/i5/i3/Pentium Processor

• **Chipset**

INTEL® H61 Chipset

• **Memory**

2 * 240 pin 4GB 1333/1066 Dual CH DDR3 SDRAM DIMM Max. up to 16GB

| | |
|---------------------------|--|
| • Expansion Slots | 1 *PCIe x 16 |
| • Storage | 4 * Serial ATA2 3Gb/s connectors |
| • Audio | Realtek ALC662 6-Channel HD Audio CODEC |
| • Ethernet LAN | Realtek RT8111EVL Gigabit Ethernet LAN |
| • USB | Embedded 7 * USB 2.0/1.1 |
| • Special Features | Support ACPI S3 Support CPU Smart FAN Support Watch Dog |
| • Rear Panel I / O | 3 * USB 2.0/1.1 ports 1 * RJ-45 port 4 * COM ports 1 * DVI-D port 1 * VGA port 3 * Audio Phone Jack |
| • Internal I / O | 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports CPU /NB / Chassis Fan connectors 1 * GPIO header 1 * Parallel header 2 * COM headers (COM6 for RS232/422/485) 1 * CIR header 1 * TPM header 1 * Chassis Intrusion header 1 * FP AUDIO header 1 * 24-pin & 4-pin 12V ATX Power connector |
| • BIOS | AMI EFI 64MB SMT Flash ROM |
| • Form Factor | Mini-ITX Form Factor (170mm x 170mm) |
| • Functional | ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation |
| • Certificate | CE, FCC, RoHS |

- **Temperature**

Operating within 0~60 centigrade

Storage within -20-85 centigrade

Product Accessories

- 2x COM cable
- Manual
- CD
- 2x SATA cable
- I/O shield