



215.00 EUR

incl. 19% VAT, plus shipping

Support:  [Specifications \[EN\]](#)

- INTEL® Cedar Trail-M Processor N2600 + NM10 Chipset
- Support 1 * DDR3 800MHz Single CH up to 2GB
- Support DirectX 9 Graphics up to 640MHz
- Support 1 * Serial ATAII (3Gb/s) Devices
- Support Dual Gigabit LAN
- Support DVI-I Output
- Equipped with 802.11 b/g/n WiFi card & Internal Antenna (JBC362F36W-2600-B only)
- Support 2.5" SATA HDD
- Support Mini PCI-E socket
- Support CFast card socket

CPU

INTEL® Cedar Trail-M Processor N2600
(1.6GHz)

INTEL® Cedar Trail-M Processor N2800
(1.86GHz)

Chipset

INTEL®NM10 Express chipset

Memory

1 * DDR3 800MHz Single CH SO-DIMM up to
2GB (For Cedar Trail-M N2600)

1 * DDR3 1066MHz Single CH SO-DIMM up to
4GB (For Cedar Trail-M N2800)

Expansion Slots	1 * MINI PCI-E
Storage	1 * Serial ATAll 3Gb/s connectors 1 * CFast card socket
Audio	Realtek ALC662 HD Audio CODEC with 4-Channel
Ethernet LAN	2 * RTL8111E PCI-EVL Gigabit LAN
USB	Embedded 7 * USB 2.0/1.1
LVDS	Onboard 1 * 24-bits Dual channel & 1 * 18-bits Single LVDS connectors
Rear Panel I / O	4 * USB 2.0/1.1 ports 2 * RJ-45 ports Line-out port 1 * DVI-I port 1 * 12V DC-IN JACK
Internal I / O	2 * USB 2.0 header for 3 * USB 2.0 ports 1 * Audio header System/Chassis/NB Fan Connectors 1 * GPIO header 1 * CFast card reader socket DIY switch x2 (reset & power button) 4 * COM header (COM1~3 for RS232,COM4 for RS232/422/485)
BIOS	AMI 16MB SMT Flash ROM
Form Factor	3.5" SBC form factor (148mmx102mm)
Certificate	CE,FCC,RoHS,ERP
Functional	ATM, Automation, Medical Equipment, Security, General Application, Transportation, Digital Signage, Kiosk, POS machine, LCD TV PC, Embedded Fanless application

Temperature

Operating within 0~60 centigrade

Storage within -20-85 centigrade

Product Accessories

- DVI-I to CRT Converter
- Manual
- CD
- 1x SATA cable
- SATA power cable
- 4x COM cable