



79.00 EUR

incl. 19% VAT, plus shipping

- **SATA !**
- **Blu-ray !**

System Interface

Data transfer speed

Max. 150 MB/s

Performance

CD

Key: insert "Max X" speed for each media below. For CD 1X=150 KB/s; DVD 1X=1350 KB/s; BD 1x = 4.5 MB/s

Read Max.24X

Digital Audio Extraction (DAE) Max.20X

Write CD-R Max.24X

Write CD-RW Max.16X

DVD

	Read (Single Layer / Dual or Double Layer)	Max. 8X/6X
	Write DVD+/-R	Max.8X
	Write DVD+R Double Layer	Max.4X
	Write DVD-RAM	Max.5X
	Write DVD+RW	Max.8X
	Write DVD-RW	Max.6X
BD		
	Read BD-ROM	Max. 6X
	Write BD-R	Max. 6X/4X
	Write BD-RE	Max. 2X/2X
Power Consumption	Typical	1100 mA
Acoustic noise	Operating (Sound pressure level, typical)	less than 50 dBA
Power supply	Voltage	DC5V +/-0.25V
Temperature	Operating C (F)	5 °C ~ 50 °C (41 °F ~ 122 °F)
	Non-operating C (F)	-40 °C ~ 65 °C (-40 °F ~ 149 °F)
Relative Humidity	Operating (No condensation)	10 % ~ 90 %
	Non-operating (No condensation, Power Off, without disc)	5 % ~ 95 %
Altitude	Operating m (ft)	-200 m ~ 3,048 m (-656 ~ 10000 ft)
	MTBF:	60,000 h (Duty:20 %)

Dimensions and weight

Width mm (in)	128 mm (5.04 in)
Depth mm (in)	127.0 mm (5.00 in) except bezel
Height mm (in)	12.7 mm (0.5 in)
Weight g	185 g +/-10 g