



149.00 EUR

incl. 19% VAT, plus shipping

- INTEL® Cedar Trail-M Processor N2600 + NM10 Chipset
- Support 1 \* DDR3 800MHz Single CH up to 2GB
- Support DirectX 9 Graphics up to 640MHz
- Support 1 \* Serial ATAII (3Gb/s) Devices
- Support Dual Gigabit LAN
- Support DVI-I Output
- Equipped with 802.11 b/g/n WiFi card & Internal Antenna (JBC362F36W-2600-B only)
- Support 2.5" SATA HDD
- Support Mini PCI-E socket
- Support CFast card socket

#### **CPU**

INTEL® Cedar Trail-M Processor N2600  
(1.6GHz)

INTEL® Cedar Trail-M Processor N2800  
(1.86GHz)

#### **Chipset**

INTEL®NM10 Express chipset

#### **Memory**

1 \* DDR3 800MHz Single CH SO-DIMM up to  
2GB (For Cedar Trail-M N2600)

1 \* DDR3 1066MHz Single CH SO-DIMM up to  
4GB (For Cedar Trail-M N2800)

#### **Expansion Slots**

1 \* MINI PCI-E

<b>Storage</b>	1 * Serial ATAll 3Gb/s connectors 1 * CFast card socket
<b>Audio</b>	Realtek ALC662 HD Audio CODEC with 4-Channel
<b>Ethernet LAN</b>	2 * RTL8111E PCI-EVL Gigabit LAN
<b>USB</b>	Embedded 7 * USB 2.0/1.1
<b>LVDS</b>	Onboard 1 * 24-bits Dual channel & 1 * 18-bits Single LVDS connectors
<b>Rear Panel I / O</b>	4 * USB 2.0/1.1 ports 2 * RJ-45 ports Line-out port 1 * DVI-I port 1 * 12V DC-IN JACK
<b>Internal I / O</b>	2 * USB 2.0 header for 3 * USB 2.0 ports 1 * Audio header System/Chassis/NB Fan Connectors 1 * GPIO header 1 * CFast card reader socket DIY switch x2 (reset & power button) 4 * COM header (COM1~3 for RS232, COM4 for RS232/422/485)
<b>BIOS</b>	AMI 16MB SMT Flash ROM
<b>Form Factor</b>	3.5" SBC form factor (148mmx102mm)
<b>Certificate</b>	CE,FCC,RoHS,ERP
<b>Functional</b>	ATM, Automation, Medical Equipment, Security, General Application, Transportation, Digital Signage, Kiosk, POS machine, LCD TV PC, Embedded Fanless application
<b>Temperature</b>	Operating within 0~60 centigrade Storage within -20-85 centigrade

**Product Accessories**

- DVI-I to CRT Converter
- Manual
- CD
- 1x SATA cable
- SATA power cable
- 4x COM cable