



199.00 EUR

incl. 19% VAT, plus shipping

Support:  [Specifications](#)

Compatible CPUs a.o. : R-464L, R-460H, R-272F, R-268D, R-460L, R-452L, R260H, R-252F

- AMD eTrinity Processor (FS1r2 Socket) with A75 FCH (Hudson D3) Chipset
 - Support DirectX 11 3D Graphics Acceleration
 - Support 6 * Serial ATA3 (6Gb/s) Devices with RAID 0, 1 & 10
 - Support SO-DIMM DDR3 1600 Dual Channel up to 16GB
 - Integrated Realtek ALC662 HD Audio CODEC with 6-CH
 - Support DP & HDMI Output
 - Supports 2 * Realtek RT8111EVL Gigabit LAN
 - Support CPU Smart FAN
 - Mini-ITX Form Factor(170mm x 170mm)
- | | |
|--|--|
| <ul style="list-style-type: none">• CPU• Chipset• Memory• Expansion Slots | <ul style="list-style-type: none">• Support AMD eTrinity Processor (FS1r2 Socket)• AMD A75 FCH Hudson D3 Chipset• 2 * SODIMM Sockets for un-buffered Dual Channel DDR3 1600 SDRAM up to 16 GB• 1 * PCI x 16 slot• 1 * Mini PCI-E |
|--|--|

- Storage
 - 6 * Serial ATA3 6Gb/s connectors support RAID 0, 1 & 10 functions
- Audio
 - Realtek ALC662 6-Channel HD Audio CODEC
- Ethernet LAN
 - 2 * Realtek RTL8111EVL PCI-E LAN chip for Gigabit LAN
- USB
 - Embedded 4 * USB 3.0 & 8 * USB 2.0/1.1
- Rear Panel I / O
 - 2 * USB 3.0 & 4 * USB 2.0/1.1 ports
 - 2 * RJ-45 ports
 - 1 * Audio I / O port
 - 1 * VGA port
 - 1 * DP port
 - 1 * HDMI port
 - 2 * COM ports
- Internal I / O
 - 2 * USB 3.0 & 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports
 - 1 * KB/MS header
 - CPU / Chipset / Chassis Fan connectors
 - 1 * GPIO header
 - 1 * 24-pin & 4-pin 12V ATX Power connector
 - 1 * TPM 1.2 header
 - 4 * COM header (COM6 for RS232/422/485)
 - 1 * CIR header
 - 1 * AUDIO header
 - 1 * Chassis Intrusion header
- BIOS
 - AMI EFI 64MB SPI Flash ROM
- Certificate
 - CE,FCC,RoHS,EuP
- Functional
 - Digital Signage, Gaming Machine, POS Machine
- Temperature
 - Operating within 0~50 centigrade
 - Storage within -20-85 centigrade
- Form Factor
 - Mini ITX Form Factor(170mmx170mm)