



249.00 EUR

incl. 19% VAT, plus shipping



Support:  [Datasheet](#)

- INTEL® Cedar Trail-D Processor D2550 + ICH10R Chipset
- Support 2 * DDR3 1066MHz Single CH up to 4GB
- Support 5 * Serial ATAII (3Gb/s) with RAID 0, 1, 5 & 10
- Realtek ALC662 6-CH HD Audio CODEC
- 1 * 24 bits Dual Channel LVDS header
- Supports 1 * Intel 82574L Gigabit LAN
- Supports JetWay 2nd Gen. Daughter Board (4x PCI Express interface)
- Support Watch dog Technology
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)

JetWay JNF9I-2550 also supports the following daughter boards:

1. JADE4RTLNG: 4x Realtek GBe LAN (PCI Express)
2. JADE4INLANG: 4x Intel GBe LAN (PCI Express)
3. JADE4COMCB: 4x Serial Ports
4. JADE4NV13M: NVIDIA NV13M, with 1GB DDR3 on board, DVI-I, HDMI and Display port output

- **CPU**
 - INTEL® Cedar Trail-D Processor D2550 CPU (1.86GHz)
- **Chipset**
 - INTEL® ICH10R Express chipset

- **Memory**
 - 2 * DDR3 1066MHz Single CH SO-DIMM up to 4GB
- **Expansion Slots**
 - 1 * PCI slot
 - 1 * full size MINI PCI-E
- **Storage**
 - 5 * Serial ATAII 3Gb/s with RAID 0, 1, 5 & 10
 - 1 * mSATA (Selectable with Mini PCI-E)
- **Audio**
 - Realtek ALC662 6-CH HD Audio CODEC
- **Ethernet LAN**
 - 1 * Intel 82574L PCI-E Gigabit LAN
- **LVDS**
 - Onboard 24-bits Dual channel connector
- **USB**
 - Embedded 10 * USB 2.0/1.1
- **Special Features**
 - Support ACPI S3
 - Support CPU Smart FAN
 - Support Watch Dog
- **Rear Panel I / O**
 - 4 * USB 2.0/1.1 ports
 - 1 * PS/2 port
 - 1 * RJ-45 port
 - 1 * COM port (COM1 for RS232/422/485)
 - 1 * VGA port
 - 1 * HDMI Port
 - 3 * Audio phone jack
- **Internal I / O**
 - 3 * USB 2.0/1.1 headers for 6 USB 2.0 ports
 - 1 * Parallel header
 - CPU /NB / Chassis Fan connectors;
 - 1 * GPIO header & 1 Parallel headers
 - 1 * COM header
 - 1 * Chassis Intrusion header
- **BIOS**
 - AMI 16MB UEFI DIP Flash ROM
- **Form Factor**
 - Mini ITX Form Factor(170mm x 170mm)
- **Functional**
 - NAS, Storage, Networking Appliance, NVR, DVR
- **Certificate**
 - CE, FCC, RoHS
- **Temperature**
 - Operating within 0~60 centigrade
 - Storage within -20-85 centigrade