



249.00 EUR

incl. 19% VAT, plus shipping

- **NVIDIA 610M GPU !**
- **5x SATA !**



- INTEL® Cedar Trail-D Processor D2550 + ICH10R Chipset + NVIDIA® 610M GPU
- Support 2 * DDR3 1066MHz Single CH up to 8GB
- Support DirectX 11 Graphics up to 850MHz
- 5 ports Serial ATAII (3Gb/s) with RAID 0, 1, 5,10 supported
- Realtek ALC887 8-CH HD Audio CODEC
- Support HDMI, DP & DVI-I (Dual Link) Display output
- Supports 1 * Realtek RT8111F Gigabit LAN
- Support Watch dog Technology
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)

• **CPU**

- INTEL® Cedar Trail-D Processor D2550 CPU (1.86GHz)

• **Chipset**

- INTEL® ICH10R Express chipset

• **GPU**

- Nvidia 610M

• **Memory**

- 2 * DDR3 1066/800MHz Single CH SO-DIMM up to 8GB

- **Expansion Slots**
 - **Storage**
 - **Audio**
 - **Ethernet LAN**
 - **USB**
 - **Special Features**
 - **Rear Panel I / O**
 - **Internal I / O**
 - **BIOS**
 - **Form Factor**
 - **Functional**
 - **Certificate**
 - **Temperature**
- 1 * MINI PCI-E
 - 5 * Serial ATAII 3Gb/s with RAID 0,1, 5, 10 supported
 - 1 * mSATA (Selectable with Mini PCI-E)
 - Realtek ALC887 8-CH HD Audio CODEC
 - 1 * RTL8111F PCI-E Gigabit LAN
 - Embedded 8 * USB 2.0/1.1
 - Support ACPI S3
 - Support CPU Smart FAN
 - Support Watch Dog
 - 4 * USB 2.0/1.1 ports
 - 1 * RJ-45 port
 - 2 * COM ports
 - 1 * DP port
 - 1 * HDMI port
 - 1 * DVI-I (Dual Link) port
 - 1 * Audio I/O port
 - 1 * +12V DC-in jack
 - 2 * USB 2.0/1.1 headers for 4 USB 2.0 ports
 - CPU /NB / Chassis Fan connectors;
 - 1 * GPIO header
 - 1 * TPM header
 - 1 * CIR
 - 1 * Chassis Intrusion header
 - AMI 16MB UEFI DIP Flash ROM
 - Mini ITX Form Factor(170mm x 170mm)
 - POS, Digital Signage, Gaming Machine, Kiosk
 - CE, FCC, RoHS
 - Operating within 0~60 centigrade
 - Storage within -20-85 centigrade