



179.00 EUR

incl. 19% VAT, plus shipping



- INTEL® Pineview-D + NM10 Chipset
- Support INTEL®ATOM D525 Dual-Core (1.83GHz) CPU
- Supports 2 * Gigabit LAN
- Integrated Realtek ALC662 HD Audio Code with 6-Channel
- Support Watch dog Technology
- Compliance with ERP standard
- Mini-ITX Form Factor(170mm x 170mm)
- Support Daughter board Expansion
- **CPU**
 - INTEL ® Atom Dual-Core Processor D525 (45nm,1.80GHz,1024MB L2 Cache)
- **Chipset**
 - INTEL®Atom D525 + NM10 chipset
 - Build-in INTEL®GMA 3150 Graphics Core (DVMT Max. 384MB)
- **Memory**
 - 2 * DDR3 800MHz Single CH SO-DIMM up to 4GB
- **Expansion Slots**
 - 1 * PCI slot
 - 1 * Mini PCI-E socket

- **Storage**
 - 4 * Serial ATA2 3Gb/s connectors support RAID 0, 1, JBOD
 - 1 * IDE connector
- **Audio**
 - Realtek ALC662 HD Audio Code with 6-Channel
- **Ethernet LAN**
 - Realtek RTL8111EVL PCI-E Gigabit Ethernet LAN
- **USB**
 - Embedded 7 * USB 2.0/1.1
 -
- **Special Features**
 - Support ACPI S3
 - Support CPU Smart FAN & DC FAN
- **LVDS**
 - Onboard 18-bit Single Channel LVDS connector
- **Rear Panel I / O**
 - 4 * USB 2.0/1.1 ports
 - 1 * PS/2 KB/MS connector
 - 2 * RJ-45 port
 - 1 * Audio I/O port (Line-in, MIC and Line-out)
 - 1 * VGA port
 - 1 * COM port
- **Internal I / O**
 - 3 * USB 2.0 ports
 - CPU / Chassis Fan connectors
 - 1 * 24-pin ATX Power connector
 - 1 * COM header (COM2 for RS-232/422/485)
 - 1 * AUDIO_IN header
 - 1 * Parallel header
 - 1 * GPIO header
- **BIOS**
 - Award 8MB DIP-SPI Flash ROM
- **Functional**
 - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Transportation, Financial Application
- **Packing**
 - Color Box Dimension : 200(W) x 200(D) x 70(H)mm
 - Cases Gross Weight : 15.4KGS
 - Cases Net Weight : 10.3KGS
 - 20 PCS / Cases, Case size : 720(L) x 410(W) x 200(H)mm
- **Certificate**
 - CE, FCC, RoHS
- **Temperature**
 - Operating within 0~60 centigrade
 - Storage within -20-85 centigrade
- **Form Factor**
 - Mini ITX Form Factor(170mmx170mm)