



44.95 EUR

incl. 19% VAT, plus shipping

- **G-Sensor !**
- **u-blox6 !**

Support: [Driver \(Windows\)](#)

VDB-800SG is new generation GPS Module, integrated G-Sensor technology.

Product Features

- 50-channel u-blox6 Engine with Over 2 Million Effective Correlators
- -146dBm SuperSense® Acquisition and Tracking Sensitivity
- AssistNow Online and Offline A-GPS Services, OMA SUPL Compliant
- 5 Hz Position Update Rate
- Highly Accurate and Reliable Navigation Performance
- Automatic Sensor Calibration and Temperature
- Operating Temperature : -40°C to 85°C
- Time To First Fix (TTFF) : <1 sec
- Standard Mini PCIe V1.2 Full-Mini Card (USB 2.0 Interface)

Receiver Type

Chipset

u-blox6 LEA-6S

Frequency	GPS L1, C/A Code GALILEO L1 Open Service (with upgrade) SBAS : WAAS, EGNOS, MSAS, GAGAN
Channels	Supports 50 Channels
Sensitivity	
Tracking & Navigation	-160dBm
Acquisition	-160dBm
Cold Start (Autonomous)	-147dBm
Time to First Fix (TTFF)	
Cold Start	28 sec
Warm Start	28 sec
Hot Start	<1 sec
Aided Start	<1 sec
Accuracy	
Horizontal Position	Position : <2.5m CEP, SBAS : <2.0m CEP
Accuracy of Timepulse Signal	RMS 30ns
Max Navigation	99% <60ns
Update Rate	5 Hz (Max.)
Dynamic Conditions	
Horizontal Position	<500 m/s (972 knots)
Accuracy of Timepulse Signal	<= 4g
G-Sensor	
3-axis accelerometer	
Output Message Format	
GPS Protocol	NMEA, UBX Binary, GGA, GLL, GSA, GSV, RMC, VTG, TXT
Multipath Suppression	
Intelligent multipath detection and suppression	
A-GPS	
Supports AssistNow® Online and Offline, OMA SUPL Compliant	
Environmental Characteristics	
Operating Temp.	-40°C to +85°C
Storage Temp.	-40°C to +85°C
Peak Supply Current	Max=150mA
Max Performance	Acquisition =74mA
Eco Mode	Tracking = 43mA
Power Input	3.3V +/-10% VDC input
Dimensions	51 x 30 (mm)
Ordering Information	
Part Number	VDB-800SG-000
Description	Embedded u-blox6 GPS with G-Sensor Mini PCIe Card