



999.00 EUR

incl. 19% VAT, plus shipping



- INTEL® LGA 1155 Processor + B85 Chipset
- Support 2 \* DDR3 1600/1333MHz Dual CH up to 16GB
- Support DirectX 9 Graphics
- Support 2 \* Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 6-CH
- 1 \* 24 bits Dual Channel LVDS header
- Supports 1 \* Intel i217LM Gigabit LAN
- Support 6 \* COM ports (COM1 support RS232/422/485)
- Support Windows 8
- Support Watch dog Technology
- Provides AT mode power
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)
- **CPU**
- **Chipset**
- INTEL® LGA1150
- INTEL® B85 chipset

- **Memory**
  - 2 \* DDR3 1600/1333MHz Dual CH SO-DIMM up to 16GB
- **Expansion Slots**
  - 1 \* PCI –E x 16 slot
- **Storage**
  - 2 \* Serial ATA3 6Gb/s connectors
  - 1 \* mSATA full size slot (Share W/Mini PCI-E slot)
- **Audio**
  - Realtek ALC662 6-Channel HD Audio
- **Ethernet LAN**
  - 1 \* INI217LM PCI-E Gigabit LAN
- **LVDS**
  - Onboard 1 \* 24-bits Dual channel connector
- **USB**
  - Embedded 6 \* USB 2.0/1.1 / 2\* USB 3.0
- **Special Features**
  - Support ACPI S3
  - Support CPU Smart FAN
  - Support Watch Dog
- **Rear Panel I/O**
  - 2 \* USB 2.0/1.1 ports
  - 2 \* USB 3.0 ports
  - 1 \* RJ-45 port
  - 3 \* Audio I/O ports ( Line-in, MIC and Line-out )
  - 3 \* VGA ports
  - 3 \* COM ports (COM1 for RS232/422/485)
- **Internal I/O**
  - 2 \* USB 2.0/1.1 headers for 4 USB 2.0 ports
  - 3 \* COM ports header
  - 2 \* NB / Chassis Fan connectors
  - 1 \* LVDS headers /1 \* Inverter headers
  - 1 \* AUDIO header
  - 1 \* HDMI-SPDIF header
  - 1 \* PS/2 header
  - 1 \* TPM header
  - 1 \* GPIO header
  - 1 \* AT mode selectable header
  - 1 \* Chassis Intrusion
- **BIOS**
  - AMI 64MB UEFI DIP Flash ROM
- **Functional**
  - POS Machine
- **Packing**
  - Color Box Dimension : 200(W) x 200(D) x 70(H)mm
- **Certificate**
  - CE, FCC, RoHS
- **Temperature**
  - Operating within 0~40 centigrade
  - Storage within -20-85 centigrade
- **Form Factor**
  - Mini ITX Form Factor(17cmx17cm)