



219.00 EUR

incl. 19% VAT, plus shipping



- Intel® H81 Chipset
 - Supports Intel LGA 1150 Socket 4th Generation Core™ i3, i5, i7 & Pentium Processors
 - 2 * Dual Channel SO-DIMM DDR3-1333/1600 up to 16GB
 - 1*HDMI output
 - Support CPU Smart FAN
 - Supports 1 * Gigabit LAN
 - Supports ACPI S3 Function
 - Support Watch dog Technology
 - Thin Mini ITX form factor
- | | |
|--|--|
| <ul style="list-style-type: none">• CPU | <ul style="list-style-type: none">• INTEL® LGA 1150 Socket 4th generation Core i7/i5/i3/Pentium Processor |
| <ul style="list-style-type: none">• Chipset | <ul style="list-style-type: none">• INTEL® H81 Chipset |
| <ul style="list-style-type: none">• Memory | <ul style="list-style-type: none">• 2 * SO-DIMM Sockets Dual Channel DDR3 1600/1333 SDRAM up to 16 GB |
| <ul style="list-style-type: none">• Expansion Slots | <ul style="list-style-type: none">• 1 *PCIe x 1• 1 * half size Mini PCI-E socket |
| <ul style="list-style-type: none">• Storage | <ul style="list-style-type: none">• 1 * Serial ATA2 3Gb/s & 1 * Serial ATA3 6Gb/s connectors• 1 * full size mSATA socket (only mSATA) |

- **Audio**
 - **Ethernet LAN**
 - **USB**
 - **Special Features**
 - **Rear Panel I / O**
 - **Internal I / O**
 - **BIOS**
 - **Form Factor**
 - **Functional**
 - **Certificate**
 - **Temperature**
- Realtek ALC662 6-Channel HD Audio CODEC
 - Intel i217LM Gigabit Ethernet LAN *1
 - 6* USB 2.0/1.1 & 2 * USB3.0
 - Support ACPI S3
 - Support CPU Smart FAN
 - Support Watch Dog
 - 2 * USB 2.0/1.1 & 2 * USB 3.0 ports
 - 1 * HDMI
 - 1 * DVI-I port
 - 1 * 19V DC-in jack
 - 1 * RJ-45 port
 - 1 * MIC-in & 1 * Line-out jacks
 - 2 * USB 2.0/1.1 headers
 - CPU /System Fan connectors;
 - 1 * PS/2 header
 - 1 * 24-bits Dual CH LVDS & 1 * Inverter connector
 - 1 * CIR header
 - 1 * AUDIO header
 - 1 * Speaker header
 - 1 * DMIC header
 - 1 * Front panel header
 - 1 * FPD Brightness connector
 - 1 * 2-pin ATX Power header
 - 1 * 2-pin open case header
 - AMI 64Mb DIP Flash ROM
 - Thin Mini ITX Form Factor (170mm x 170mm)
 - ATM, POS, AIO, Panel PC, Digital Signage
 - CE, FCC, RoHS
 - Operating within 0~60 centigrade
 - Storage within -20-85 centigrade