



329.00 EUR

incl. 19% VAT, plus shipping

- INTEL® Celeron-M Processor 1047UE + HM65 Chipset
- Support 1 \* DDR3 1066/1333MHz Single CH up to 8GB
- Support 1 \* Serial ATAIII (6Gb/s) Devices
- Support CFast card
- Support mSATA card (Share with Mini PCI-E)
- Support Mini PCI-E x 1
- 1 \* 24 bits Dual Channel LVDS header
- Support DVI-I Output
- Supports 2 \* Realtek RTL8111F-CG Gigabit LAN
- Support CPU Smart FAN

- |                            |  |
|----------------------------|--|
| • <b>Dimension (W*H*D)</b> | • 185 * 60 * 142 mm  |
| • <b>Construction</b>      | • Aluminum housing   |
| • <b>Colors</b>            | • Black / HBJC381F39-1047-B  |
| • <b>MB model</b>          | • JNF39-1047 (3.5 " SBC)   |
| • <b>CPU &amp; CHIP</b>    | • INTEL® Celeron-M Processor 1047UE + HM65 Chipset   |
| • <b>BIOS</b>              | • AMI 32MB SMT Flash ROM   |
| • <b>Memory</b>            | • 1 * SO-DIMM slot (DDR3-1333/1600Mhz_Max 8GB)   |
| • <b>Storage Space</b>     | • 1 * 2.5" SATA Device (Support SATA 6G / Max Height 9.5 mm)<br>• 1 * m-SATA SSD Device (Mini PCI-E)<br>• 1 * CFast card |
| • <b>Display Interface</b> | • 1 * DVI-I<br>• 1 * LVD-24 bits ( Internal pin header)  |

- **Network**
  - 2 \* RJ45 (RTL8111F-CG Gigabit LAN)
  - WiFi (optional / JBC381F39W-1047-B)
- **Audio**
  - 2 \* Line out
  - 1 \* Mic in
- **Front I/O Port**
  - 2 \* USB 2.0
  - 2 \* COM (Max 4 Ports)
- **Rear I/O Port**
  - 4 \* USB 2.0
- **Expansion Interface**
  - 1 \* Mini PCI-E (Full-size)
- **Power Source**
  - DC-12V Jack input
  - Adapter : AC\_90~240V / DC\_12V\_5A / 60W
- **Certification**
  - EMC : CE , FCC
  - Safety : RoHS , ErP
- **Environment**
  - Operating Temperature : 0 ~ 40°C
  - Storage Temperature : 0 ~ 60°C
  - Vibration During Operation : N/A
  - Shock During Operation : N/A
- **Mounting**
  - Wall mounting Kits
- **Packing**
  - Net Weight : 2.2KG
  - Gross Weight : 3.5KG
  - Color Box Dimension : 250(W) x 118 (D) x 295 (H) mm