



309.00 EUR

incl. 19% VAT, plus shipping

- Intel Celeron Processor BayTrail-M N2910/N2920
- 2 \*DDR3L 1066MHz Single CH SO-DIMM up to 8GB
- Support 2 \* Serial ATAll (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- Integrated 1 \* 24-bits Dual CH LVDS
- Supports 1 \* Realtek RT8111G Gigabit LAN
- Support CPU Smart FAN
- Support Watch dog Technology
- Thin Mini-ITX Form Factor(17cm x 17cm)
- Slim & Fanless design, within 2cm height

• **CPU**

- Intel Celeron Processor BayTrail-M N2910/ N2920

• **Chipset**

- INTEL® Bay Trail-M SoC Processor

• **Memory**

- 2 \*DDR3L 1333/1066MHz Single CH SO-DIMM up to 8GB

• **Expansion Slots**

- 1 \* PCI-E x 1 slot
- 1 \* MINI PCI-E

• **Storage**

- 2 \* Serial ATAll (3Gb/s) connectors (One share with mSATA)
- 1 \* mSATA socket (Share with one SATA port)

• **Audio**

- Realtek ALC662 2-Channel HD Audio

• **Ethernet LAN**

- 1 \* RTL8111G PCI-E Gigabit LAN

• **LVDS**

- 1 \* 24-bits Dual CH LVDS connector

• **USB**

- Embedded 3 \* USB 3.0 + 5 \* USB 2.0/1.1

- **Special Features**
  - Support ACPI S3
  - Support CPU Smart FAN
  - Support Watch Dog
- **Rear Panel I / O**
  - 1 \* USB 3.0 port
  - 3 \* USB 2.0/1.1 ports
  - 1 \* RJ-45 port
  - 1 \* DVI-I port
  - 1 \* COM port (Support RS232/422/485)
  - 1 \* Line-out connector
  - 1 \* 4-pin 9V~36V DC in jack
- **Internal I / O**
  - 1 \* USB 3.0 header for 2 USB 3.0 ports
  - 1 \* USB 2.0/1.1 header for 2 USB 2.0 ports
  - 1 \* KB/MS header
  - CPU smart Fan / System Fan headers
  - 1 \* LVDS header & 1 \* GPIO header & 1 Parallel header
  - 3 \* COM headers & 4 \* COM ports 5V/12V Selectable headers
  - 1 \* AUDIO AMP & 1 \* AUDIO header & 1 \* SPDIF header
  - 1 \* chassis intrusion header & 1 \* AT mode selectable header
- **BIOS**
  - AMI 64MB SMT Flash ROM
- **Form Factor**
  - Thin Mini ITX Form Factor (170mm x 170mm)
- **Functional**
  - Panel PC, ATM, Security, KIOSK, POS, General Application, Transportation
- **Certificate**
  - CE, FCC, RoHS
- **Temperature**
  - Operating within 0~60 centigrade
  - Storage within -20-85 centigrade