



289.00 EUR

incl. 19% VAT, plus shipping

- INTEL® Bay Trail-M N2930 SoC Processor (QC, 1.83G)
INTEL® Bay Trail-I E3827 SoC Processor (DC, 1.75G)
- Support 1 * DDR3L 1333/1066MHz Single CH up to 4GB
- Support 1 * Serial ATAll (3Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- 1 * 24 bits Dual Channel LVDS header
- Support DVI-I Output
- Supports 2 * Realtek RT8111G Gigabit LAN
- Support CPU Smart FAN
- 148 x 102mm 3.5" SBC Form Factor

CPU	INTEL® Bay Trail-M N2930 SoC Processor (QC, 1.83GHz)
Chipset	N/A
Memory	1 * DDR3L 1333/1066MHz Single CH SO-DIMM up to 4GB
Expansion Slots	2 * MINI PCI-E (one share with mSATA) socket
Storage	1 * Serial ATAll 3Gb/s connector 1 * mSATA socket
Audio	Realtek ALC662 HD Audio CODEC with 2-Channel

Ethernet LAN	2 * RTL8111G PCI-E Gigabit LAN
USB	Embedded 1 * USB 3.0 + 7 * USB 2.0/1.1
LVDS	Onboard 1 * 24-bits Dual channel LVDS connector
Rear Panel I / O	<ul style="list-style-type: none"> 1 * USB 3.0 port 3 * USB 2.0/1.1 ports 2 * RJ-45 ports 1 * Line-out port 1 * DVI-I port 1 * one-pin 9~24V DC-IN Jack
Internal I / O	<ul style="list-style-type: none"> 2 * USB 2.0 header for 4 * USB 2.0 ports 1 * KB/MS header 1 * Audio header & 1 * HDMI-SPDIF header Chassis Fan Connectors 1 * GPIO header 4 * COM headers (COM1 support RS232/422/485) & 4 * COM ports 5V/12V Selectable headers 1 * chassis intrusion header & 1 * AT mode selectable header
BIOS	AMI 64MB SMT Flash ROM
Form Factor	3.5" SBC form factor (148mmx102mm)
Certificate	CE,FCC,RoHS,ERP
Functional	ATM, Automation, Medical Equipment, Security, General Application, Transportation, Digital Signage, Kiosk, POS machine, LCD TV PC, Embedded Fanless application
Temperature	<ul style="list-style-type: none"> Operating within 0~60 centigrade Storage within -20-85 centigrade