



199.95 EUR

incl. 19% VAT, plus shipping

- **Intel Celeron BayTrail !**
- **Dual Gigabit LAN !**
- **Win7, Win 8 !**



- Built-in Intel[®] Celeron[™] J1900 (2.0 GHz) quad-core processor
- GIGABYTE Ultra Durable[™] 4 Plus Technology
- All Solid Capacitors with Humidity Protection New Glass Fabric PCB design
- Dual LAN with high ESD Protection
- GIGABYTE UEFI DualBIOS[™]
- DVI-D, D-SUB ports on rear panel
- Ample USB 3.0 ports with GIGABYTE 3x USB power
- GIGABYTE On/Off Charge[™] for USB devices
- Mini PCI-E expansion slot supports wireless networking cards
- PCI expansion slot supports legacy interface cards

CPU

1. Built in with an Intel[®] Celeron[®] Quad-Core J1900 SoC (2.0 GHz)
* Do not disassemble the onboard SoC and the heatsink by yourself to avoid damage to these components.
2. 2 MB Cache

Memory

1. 2 x DDR3/-L SO-DIMM sockets supporting up to 8 GB of system memory
 - * If only one DDR3/-L memory module is to be installed, be sure to install it in the SODIMM_1 socket.
2. Dual channel memory architecture
3. Support for DDR3/-L 1333 MHz memory modules
4. Support for non-ECC memory modules

Onboard Graphics

Integrated in the SoC:

1. 1 x D-Sub port, supporting a maximum resolution of 2560x1600
2. 1 x DVI-D port, supporting a maximum resolution of 1920x1080
 - * The DVI-D port does not support D-Sub connection by adapter.

Audio

1. Realtek[®] ALC887 codec
2. High Definition Audio
3. 2/4/5.1/7.1-channel * To configure 7.1-channel audio, you have to use an HD front panel audio module and enable the multi-channel audio feature through the audio driver.
4. Support for S/PDIF Out

LAN

1. 2 x Realtek[®] GbE LAN chips (10/100/1000 Mbit)

Expansion Slots

1. 1 x PCI slot
2. 1 x Mini PCI Express x1 slot
(The Mini PCI Express slot conforms to PCI Express 2.0 standard.)
(For Mini-PCIE card/no mSATA card)

Storage Interface

Integrated in the SoC:

1. 2 x SATA 3Gb/s connectors

USB

Integrated in the SoC:

1. 2 x USB 2.0/1.1 ports (available through the internal USB header)

SoC + Renesas[®] uPD720210 USB 3.0 Hub:

1. 4 x USB 3.0/2.0 ports on the back panel

Internal I/O Connectors

1. 1 x 24-pin ATX main power connector
2. 1 x 4-pin ATX 12V power connector
3. 2 x SATA 3Gb/s connectors
4. 1 x CPU fan header
5. 1 x system fan header
6. 1 x front panel header
7. 1 x front panel audio header
8. 1 x S/PDIF Out header
9. 1 x USB 2.0/1.1 header
10. 1 x parallel port header
11. 1 x Clear CMOS jumper
12. 1 x chassis intrusion header
13. 1 x debug card header

Back Panel Connectors

1. 1 x PS/2 keyboard port
2. 1 x PS/2 mouse port
3. 1 x D-Sub port
4. 1 x DVI-D port
5. 2 x serial ports
6. 4 x USB 3.0/2.0 ports
7. 2 x RJ-45 ports
8. 3 x audio jacks (Line In, Line Out, Mic In)

I/O Controller

1. iTE[®] I/O Controller Chip

H/W Monitoring

1. System voltage detection
2. CPU/System temperature detection
3. CPU/System fan speed detection
4. CPU/System fan speed control
 - * Whether the fan speed control function is supported will depend on the cooler you install.

BIOS

1. 2 x 64 Mbit flash
2. Use of licensed AMI UEFI BIOS
3. Support for DualBIOS™
4. PnP 1.0a, DMI 2.7, WfM 2.0, SM BIOS 2.7, ACPI 5.0

Unique Features

1. Support for @BIOS
2. Support for Xpress Install
3. Support for APP Center
 - * Available applications in APP Center may differ by motherboard model. Supported functions of each application may also differ depending on motherboard specifications.
4. Support for ON/OFF Charge

Bundle Software

1. Norton® Internet Security (OEM version)
2. Intel® Smart Connect Technology

Operating System

1. Support for Windows 8.1/8 32-bit/64-bit
2. Support for Windows 7 64-bit
 - * To support Windows 7 64-bit, please update the latest BIOS and drivers.

Form Factor

1. Mini-ITX Form Factor; 17.0cm x 17.0cm

Remark

1. Due to different Linux support condition provided by chipset vendors, please download Linux driver from chipset vendors' website or 3rd party website.
2. Most hardware/software vendors may no longer offer drivers to support Win9X/ME/2000/XP SP1/SP2. If drivers are available from the vendors, we will update them on the GIGABYTE website.