



164.00 EUR

incl. 19% VAT, plus shipping

- Intel® Celeron™ J1900 (2.0 GHz) quad-core processor
- Support DirectX 11 3D Graphics Acceleration
- Support DDR3L 1333
- Integrated HD Audio CODEC
- Support PCI Express Gigabit LAN
- Support 1*USB3.0 Port
- Support 24-bit Dual channel LVDS
- Onboard 1*MiniPCI-E connector
- Onboard 1 *M- SATA connector
- 2 Phase CPU Power Support
- Support Thunder Protection Function
- [Thin mini ITX](#) Form Factor(170mm X170mm)

• **CPU-Chipset**

- INTEL® Celeron™ J1900 (2.0 GHz) quad-core processor
- 2 Phase CPU Power Support

• **I.O Chipset**

- Fintek F71808EC

- **Memory**
 - 2*SO-DIMM slot
 - Support DDR3L 1333
 - Max. capacity of system memory up to 16GB
- **Expansion Slots**
- **Storage**
 - 1 * MiniPCI-E connector
 - 1* Serial ATA2 3Gb/s connector(CO-LAY M-SATA)
 - 1 * [M-SATA Connector](#)
- **Audio**
 - ALC887 Audio CODEC
 - HD Audio CODEC
- **Ethernet LAN**
 - Realtek® RTL8111G Chip
 - PCI Express Gigabit LAN
- **LVDS**
 - Onboard 24-bit Dual channel
- **USB**
 - 1* USB3.0 (EXT)
 - 2* USB 2.0/1.1(2 distribute in back panel)
- **Special Features**
 - Support CPU Smart Fan
 - Support Watch dog Technology
 - Support GPIO Technology
 - Support Amplifier function(3W)
 - Thunder Protection Function
 - All Solid Capacitor design for CPU
- **Back Panel I / O**
 - 1* PS/2 port
 - 2* USB 2.0/1.1 ports
 - 1* USB 3.0 port
 - 1* RJ-45 port
 - 1* DVI port
 - 1* VGA port
 - 1* 3-JACK
- **Internal I / O**
 - 2*CPU / Chassis Fan connectors
 - 1*COM header
 - 1 *24-pin ATX Power connector
 - 1 *24-bit Dual Channel LVDS header
 - 1 *GPIO header
 - 1 *Mini PCI-e connector
 - 1 * M-SATA Connector
 - 1* SATA Connector
 - 1 * Audio header
 - 1 * Front panel header
- **BIOS**
 - AMI 64MB DIP Flash ROM
- **Form Factor**
 - Thin mini ITX Form Factor(170mm X 170mm)