



999.00 EUR

incl. 19% VAT, plus shipping



- INTEL® Haswell / Broadwell SoC Processor
- 2\* DDR3L 1333/1600 up to 16GB
- Support 1 \* Serial ATAIII (6Gb/s) Devices
- Integrated Realtek ALC662 HD Audio CODEC with 2-CH
- 1 \* 24 bits Dual Channel LVDS header
- 1 \* mPCIE
- 1 \* mSATA (share with mPCIE)
- 2 \* USB 2.0 + 4 \* USB 3.0
- 2 \* HDMI Output
- Supports 2 \* Gigabit LAN
- Support CPU Smart FAN
- DC IN Jack 9~24V

• Dimension (W\*H\*D)

• 185 \* 60 \* 142 mm

• Construction

• Aluminum housing

• Colors

• Black

• MB model

• JNF3E-4300U (3.5 " SBC)

• CPU & CHIP

• INTEL® Haswell ULT i5-4300U

• BIOS

• AMI 32MB SMT Flash ROM

- Memory
  - 2 \* SO-DIMM (DDR3-1333/1600Mhz\_Max 16GB)
- Storage Space
  - 1 \* 2.5" SATA Device (Support SATA 6G / Max Height 9.5 mm)
  - 1 \* m-SATA SSD Device (Mini PCI-E)
- Display Interface
  - 2 \* HDMI
  - 1 \* LVD-24 bits ( Internal pin header)
- Network
  - 2 \* RJ45 (I211AT + I218LM Gigabit LAN)
  - WiFi (optional / JBC382F3EW-4300UB)
- Audio
  - 1 \* Audio
- Front I/O Port
  - 2 \* USB 2.0
  - 4 \* COM
- Rear I/O Port
  - 4 \* USB 3.0
  - 2 \* USB 2.0
- Expansion Interface
  - 1 \* Mini PCI-E (Half-size)
- Power Source
  - DC-12V Jack input
  - Adapter : AC\_90~240V / DC\_12V\_5A / 60W
- Certification
  - EMC : CE , FCC
  - Safety : RoHS , ErP
- Environment
  - Operating Temperature : 0 ~ 50°C
  - Storage Temperature : 0 ~ 60°C
  - Vibration During Operation : N/A
  - Shock During Operation : N/A
- Mounting
  - Wall mounting Kits
- Packing
  - Net Weight : 2.2KG
  - Gross Weight : 3.5KG
  - Color Box Dimension : 250(W) x 118 (D) x 295 (H) mm