



649.00 EUR

incl. 19% VAT, plus shipping

- INTEL® Haswell-U / Broadwell-U SoC Processor
- Support 2 * SO-DIMM DDR3L 1333/1600 up to 16 GB
- 9~24V Wide range DC-in
- Support INTEL® i218LM Gigabit PHY LAN
- Onboard 1* Half size Mini PCIe socket
- Onboard 1*mSATA socket
- 3 * USB3.0, 2 * USB2.0
- 2 * HDMI1.4 ports
- Support slim Fan design
- NUC Form Factor(101 * 101mm)

Form Factor

Dimensions

- NUC (101 X 101 mm)

Processor System

CPU	- Intel® Haswell-U / Broadwell-U SoC Processor
Core Number	- (By CPU)
Max Speed	- (By CPU)
L2 Cache	- (By CPU)
Chipset	- SoC
BIOS	- AMI 128Mb Flash ROM

Expansion Slot

PCI	- 0
Mini-PCIe	- 1 (half size)
mSATA	- 1 (full size)
PCIe	- 0
CFast Card Socket	- 0
CF Card Socket	- 0

Memory

Technology	- Two Channel DDR3L 1333/1066 MHz SDRAM
Max.	- 16 GB
Socket	- 2 * SO-DIMM

Graphics

Controller	- Integrated Intel® HD Graphics
------------	---------------------------------

VRAM	- Shared Memory
VGA	- No
LVDS	- No
HDMI	- 2
DVI-I	- No
DisplayPort	- No
MultiDisplay	- Yes (Dual Display)

Ethernet

Ethernet	- 10/100/1000 Mbps
Controller	- GbE LAN: INTEL® 218LM
Connector	- 1 x RJ 45

SATA

Max Data Transfer Rate	- 1 x SATAIII (6.0Gb/s)
------------------------	-------------------------

External I/O

VGA	- 0
DVI-I	- 0
HDMI	- 2
DisplayPort	- 0
Ethernet	- 1

USB	- 3 (2 x USB 3.0 at rear & 1 x USB3.0 at front)
Audio	- 1 (Line-out W/SPDIF-out)
Serial	- 0
eSATA	- 0
PS2	- 0
DC-input	- +9~24V DC in Jack

Internal Connector

USB	- 2 (2 x USB 2.0)
PS/2	- 0
LVDS / inverter	- 0
VGA	- 0
Serial	- 1 (1 x RS232/422/485)
SATA	- 1
mPCIe	- 1 (half size)
Parallel	- 0
mSATA	- 1 (full size)
CIR	- 0
GPIO 8-bit	- 0
Chassis intrusion	- 1

Audio Amplifier Header - 1

AT mode jumper - 1

Watchdog Timer

Output - From Super I/O to drag RESETCON#

Interval - 256 segments, 0,1,2...255sec/min

Power Requirements

Input PWR - 9~24V DC-In
- 2-pin PWR Con

Power On AT/ATX Supported
- AT : Directly PWR on as Power input ready
- ATX: Press Button to PWR on after Power input ready

Certifications

Certifications - CE, FCC, RoHS, REACH

Environment

Temperature - Operating: 0°C– 60°C

- Storage: -20°C– 85°C