

729.00 EUR

incl. 19% VAT, plus shipping



- M/B Model: NU92-4300U
  - Embedded Core i5 NUC System
  - INTEL® Haswell Refresh Core i5 – 4300U
  - 2 \* SO-DIMM slot / DDR3L 1600 (Max to 16GB)
  - 1 \* full size Mini PCI-E slot for m-SATA Device
  - Application: Networking, Industrial Automation, I.o.T
- |   |   |
|---|---|
| <ul style="list-style-type: none"> <li>• Dimension (W*D*H)</li> <li>• Construction</li> <li>• Colors</li> <li>• MB model</li> <li>• CPU</li> <li>• BIOS</li> <li>• Memory</li> <li>• Storage Space</li> <li>• Display Interface</li> <li>• Network</li> <li>• Audio</li> <li>• Front I/O Port</li> <li>• Rear I/O Port</li> </ul> | <ul style="list-style-type: none"> <li>• 116 * 110 * 49 mm</li> <li>• Top cover &amp; I/O plate –aluminum; Base- metal</li> <li>• Black / JBC312U92(W)-4300UB</li> <li>• JNU92-4300U</li> <li>• INTEL® Haswell Refresh Core i5 – 4300U (CPU Fan / DC 5V)</li> <li>• AMI UEFI</li> <li>• 2 * SO-DIMM slot / DDR3L 1600 (Max to 16GB)</li> <li>• 1 * full size Mini PCI-E slot for m-SATA Device</li> <li>• 2 * HDMI</li> <li>• 1 * RJ45 (Giga LAN)</li> <li>• WiFi (HBJC312U92W-4300UB only)</li> <li>• 1 * Audio port</li> <li>• 1 * USB 3.0</li> <li>• 1 * COM</li> <li>• 2 * USB 3.0</li> </ul> |
|---|---|

- Expansion Slot
  - Power Source
  - Certification
  - Environment
  - Mounting Bracket
  - Packing
- 1 \* half size Mini PCI-E slot
  - DC 9-24V Jack input
  - Adapter : AC\_90~240V / DC\_12V\_3A/ 36W
  - EMC : CE , FCC
  - Safety : RoHS , ErP
  - Operating Temperature : -10°C~60°C with air flow (mSATA)
  - Storage Temperature : -20°C~80°C
  - Vibration During Operation : N/A
  - Shock During Operation : N/A
  - Wall/VESA/DIN Rail combo mounting Kit
  - Net Weight : 1.4KG
  - Gross Weight : 1.8KG
  - Color Box Dimension : 158(W) x 167(D) x 123.6(H) mm