



209.00 EUR

incl. 19% VAT, plus shipping



- Intel® Cedar Trail-D Processor D2550 + NM10 Chipset
- Support 2 * DDR3 1066MHz Single CH up to 4GB
- Support DirectX 10 Graphics up to 640MHz
- Support 2 * Serial ATAll (3Gb/s) & 2 * Serial ATAllI (6Gb/s)
- Realtek ALC662 6-CH HD Audio CODEC with 6-CH
- 1 * 24 bits Single Channel LVDS headers
- Support 2 CRT Display
- Supports 2 * Realtek RT8111EVL Gigabit LAN
- Support Watch dog Technology
- Support CPU Smart FAN
- Compliance with ErP standard
- Mini-ITX Form Factor (170mm x 170mm)
- CPU
 - Intel® Cedar Trail-D Processor D2550 (1.86GHz) CPU
- Chipset
 - Intel®NM10 Express chipset
- Memory
 - 2 * DDR3 1066MHz Single CH SO-DIMM up to 4GB

- Expansion Slots
 - 1 * PCI slot
 - 1 * Mini PCIe
- Storage
 - 2 * Serial ATAII 3Gb/s + 2 * Serial ATAIII 6Gb/s connectors
- Audio
 - Realtek ALC662 6-CH HD Audio CODEC
- Ethernet LAN
 - 2 * RTL8111EVL PCI-E Gigabit LAN
- LVDS
 - Onboard 24-bits single channel & 24-bits dual channel connectors
- USB
 - Embedded 7 * USB 2.0/1.1
 -
- Special Features
 - Support ACPI S3
 - Support CPU Smart FAN
 - Support Watch Dog
- Rear Panel I / O
 - 4 * USB 2.0/1.1 ports
 - 2 * RJ-45 port
 - 2 * COM port
 - 2 * VGA port
 - 1 * HDMI Port
 - 1 * Audio port (Line-in, MIC and Line-out)
- Internal I / O
 - 2 * USB 2.0/1.1 headers for 3 USB 2.0 ports
 - 1 * Parallel header
 - 1 * PS2/KB header
 - CPU /NB / Chassis Fan connectors;
 - 1 * GPIO header
 - 4 * COM headers(COM6 for RS232/422/485)
 - 1 * chassis intrusion header
- BIOS
 - AMI 16MB DIP Flash ROM
- Form Factor
 - Mini ITX Form Factor(170mm x 170mm)
- Functional
 - ATM, Automation, medical Equipment, Security, Networking, POS, General Application, Gaming Machine, Transportation, Kiosk
- Certificate
 - CE, FCC, RoHS
- Temperature
 - Operating within 0~60 centigrade
 - Storage within -20-85 centigrade