



439.00 EUR

incl. 19% VAT, plus shipping



- JNF532-2930 (3.5 " SBC)
 - INTEL® Bay Trail-M N2930 SoC Processor (1.83GHz)
 - 1 * SO-DDR-3 Low Voltage (Max 8GB)
 - 1 * 2.5" SATA Device (Max Height 9.5 mm)
 - 1 * m-SATA SSD Device (Mini PCI-E)
 - Application : Gaming,Medical,POS/KIOSK,Industrial Automation, Transportation,Telecom,Networking,I.O.T,AIO
- | | |
|---|---|
| <ul style="list-style-type: none"> • Dimension (W*H*D) • Construction • Colors • MB model • CPU • BIOS • Memory • Storage Space • Display Interface • Network | <ul style="list-style-type: none"> • 185 * 48 * 142 mm • Aluminum housing • Black • JNF532-2930 (3.5 " SBC) • INTEL® Bay Trail-M N2930 SoC Processor (1.83GHz) • AMI UEFI • 1 * SO-DIMM solt (Max 8GB) • 1 * 2.5" SATA Device (Max Height 9.5 mm) • 1 * m-SATA SSD Device (Mini PCI-E) • 1 * DVI-D • 1 * VGA (Internal pin header) • 2 * RJ45 (Giga Lan) • WiFi (optional / JBC375F532W-2930-B) |
|---|---|

- Audio
 - 1 * Line out
 - 1 * Mic in
- Front I/O Port
 - 2 * USB 2.0
 - 4 * COM (2x factory installation, 2x included in accessories)
- Rear I/O Port
 - 3 * USB 2.0
 - 1 * USB 3.0
 - 2 * RJ45
 - 1 * DVI-D
 - 1 * VGA
- Expansion Interface
 - Mini PCI-E # 1 : Half-size (for mini PCIE WIFI module)
 - Mini PCI-E # 2 : Full-size (for M-SATA SSD)
- Power Source
 - DC 9~24V Jack input
 - Adapter : AC_90~240V / DC_12V_5A / 60W
- Certification
 - EMC : CE , FCC
 - Safety : RoHS , ErP
- Environment
 - Operating Temperature : 0 ~ 40°C
 - Storage Temperature : -10 ~ 60°C
 - Vibration During Operation : N/A
 - Shock During Operation : N/A
- Mounting
 - Wall mounting Kits
- Packing
 - Net Weight : 1.4KG
 - Gross Weight : 2.7KG
 - Color Box Dimension : 250(W) x 118 (D) x 295 (H) mm