



999.00 EUR

incl. 19% VAT, plus shipping



- INTEL® Skylake-U(i5-6200U /i5-6300U)
  - Support 2 \* DDR4 2133MHz Dual Channel SO-DIMM, max up to 32GB
  - 1 \* 2.5" SATA Device
  - 1 \* m-SATA SSD Device (Mini PCIe)
  - 6 \* Intel® PCIe GbE LAN
  - 1 \* External COM (RJ-45), 1 \* Internal COM (Option)
  - 4 \* External USB3.0, 2 \* USB1.1/2.0, 2 \* Internal USB1.1/2.0
  - 2 \* DP (max resolution:4096 x 2304@60Hz)
  - 1 \* GPIO (8 bit programmable inputs/outputs)
  - Support CPU Smart FAN
- |  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• Product Dimension</li> <li>• Construction</li> <li>• Colors</li> <li>• Model Name</li> <li>• MB Model</li> <li>• BIOS</li> <li>• CPU</li> </ul> | <ul style="list-style-type: none"> <li>• 185 (W) * 142 (H) * 60 (D) mm</li> <li>• Aluminum housing</li> <li>• Black</li> <li>• JBC385F551-6200U-B (i5-6200U)</li> <li>• JBC385F551-6300U-B (i5-6300U)</li> <li>• JNF551-6200U</li> <li>• JNF551-6300U</li> <li>• AMI 128Mb Flash ROM</li> <li>• INTEL® Skylake-U(i5-6200U /i5-6300U), TDP: 15W</li> </ul> |
|--|---|

- Memory
  - 2 \* SO-DIMM DDR4 2133MHz (Max. 32GB)
- Storage Space
  - 1 \* 2.5" SATA Device
  - 1 \* m-SATA SSD Device (Mini PCIe)
- Front I/O Port
  - 2 \* USB 3.0
  - 1 \* COM (RJ-45 Type)
  - 6 \* RJ45 (GbE LAN: Intel i211AT/i219LM/i350AM4)
- Rear I/O Port
  - 2 \* USB 2.0
  - 2 \* USB 3.0
  - 2 \* DP (max resolution:4096 x 2304@60Hz)
  - 1 \* GPIO (8 bit programmable inputs/outputs)
  - 1 \* COM (Option)
  - WiFi (optional / JBC385F551W-6X00U-B)
- Expansion Interface
  - Mini PCIe # 1 : Full-size (for mini PCIe module)
  - Mini PCIe # 2 : Full-size (one shared with mSATA)
- Power Source
  - Lockable 12V DC-in Jack
  - Adapter: AC 90~240V / DC 12V\_5A / 60W
- Packing
  - Net Weight : 2.2KG
  - Gross Weight : 3.5KG
  - Color Box Dimension : 250 (W) x 118 (D) x 295 (H) mm
- Environment
  - Operating within 0 ~ 50°C
  - Storage within -20 ~ 70°C
- Mounting
  - Wall mounting Kits
- Certification
  - EMC : CE , FCC
  - Safety : RoHS , ErP