



279.00 EUR

incl. 19% VAT, plus shipping

- Intel® LGA1151 Socket Core i3, i5, i7 & Pentium Processors (max. 65W)
- Intel® H110 Express Chipset
- Support Dual Channel DDR4 2133MHz, 2 \* DIMM slot, up to 32GB memory
- 2 \* Realtek Gigabit LAN (RTL8111G)
- 3 \* SATA III (6Gb/s), 1 \* M.2 (M key 2242, 2260, 2280, 22110)
- 4 \* USB 3.0, 5 \* USB 2.0/1.1
- 10 \* COM ports (COM1 supports RS232/422/485)
- Support TPM 1.2 function (option)
- Micro ATX form factor (244mm x 244mm)

## Form Factor

### Dimensions

- Micro ATX (244 \* 244mm)

## Processor System

<b>CPU</b>	- Intel LGA 1151 Socket Core i7 / i5 / i3 & Pentium Processors
<b>Core Number</b>	- (By CPU)
<b>Max Speed</b>	- (By CPU)
<b>L2 Cache</b>	- (By CPU)
<b>Chipset</b>	- Intel H110 Chipset
<b>BIOS</b>	- AMI 64Mb Flash ROM

## Expansion Slot

<b>Mini-PCIe</b>	- 1 (full size)
<b>m.2</b>	- 1 (M Key 2242, 2260, 2280, 22110)
<b>PCIe</b>	- 1 * PCIe x16 & 1 * PCIe x 1
<b>PCI</b>	- 2
<b>SIM card holder</b>	- 1

## Memory

<b>Technology</b>	- Dual Channel DDR4 2133MHz
<b>Max.</b>	- 32GB
<b>Socket</b>	- 2 * DIMM

## Graphics

<b>Controller</b>	- Intel <sup>®</sup> Gen9 Graphics supports DX 11/12, OGL4.3 / 4.4
<b>VRAM</b>	- Shared Memory
<b>VGA</b>	- 1 (Max. Resolution : 1920*1200@60Hz)
<b>DVI-D</b>	- 1 (Max. Resolution : 1920*1200@60Hz)
<b>HDMI</b>	- 1 (Max. Resolution : 3840*2160@24Hz)
<b>DP</b>	- 0
<b>eDP</b>	- 0
<b>MultiDisplay</b>	- Dual Display
<b>Ethernet</b>	
<b>Ethernet</b>	- 10/100/1000 Mbps
<b>Controller</b>	- PCIe GbE LAN : Realtek RTL8111G
<b>Connector</b>	- 2 * RJ 45
<b>Audio</b>	
<b>CODEC</b>	- HD Audio : Realtek ALC662
<b>Channel</b>	- 6 Channel