



769.00 EUR

incl. 19% VAT, plus shipping

- INTEL® Broadwell I5 5200U SoC Processor
- 2 * SO-DIMM (Dual Channel DDR3L 1333/1600MHz SDRAM)
- Support CPU Smart FAN
- Giga LAN Port * 2
- Support 10/100M/1000M Base-TX RJ45 Ports * 4
- Support Watch dog Technology
- Support AC 90~240V input
- Applications : Industrial Control System,
Networking Server System、 Security Industry
- Product Dimension
 - 264 (W) * 199.4 (D) * 38 (H) mm
- Product Model
 - JBC512F3EG(W)-5200-B
- MB Model & Size
 - NF3EP-5200 / 3.5" SBC
- BIOS
 - AMI 32MB SMT Flash ROM
- CPU
 - INTEL® Broadwell I5 5200U
- Memory
 - 2 * SO-DIMM (Dual Channel DDR3L 1333/1600MHz SDRAM)
- Storage Space
 - 2.5" SATA Device * 1
- Colors
 - Black
- Front I/O Port
 - 4 PIN AC Input * 1
 - AC ON-OFF * 1
 - Power LED * 1
 - Power SW * 1
 - USB 2.0 * 2
- Rear I/O Port
 - USB3.0 * 4 , USB2.0 * 2
 - HDMI * 2
 - Giga LAN Port * 2
 - Audio * 1
 - WiFi Port * 2 (JBC512F3EGW-5200-B only)

- POE Port
 - 10/100M/1000M Base-TX RJ45 Ports * 4
 - Conforms to IEEE802.3af, IEEE802.3at
 - IEEE 802.3x full-duplex flow control, per port up to 23W
 - Provides 4 PoE injector, per port DC52.5V-0.48A-25W
 - For Switch : Marvell 88E6176
 - For PoE : MAX5980

- Power Source
 - 150W AC to DC OP Power inside
 - AC 90~240V input

- Accessory
 - AC Cable * 1
 - 4 Pin Terminal block con * 1
 - User Manual * 1
 - CD * 1
 - Screw Package * 1

- Packing
 - Net Weight : 3.6KG
 - Gross Weight : 4.5KG
 - Color Box Dimension : 406 (W) x 148 (D) x 359 (H) mm

- Temperature
 - Operating within 0~50 centigrade
 - Storage within -10-70 centigrade

- Certification
 - EMC : CE , FCC
 - Safety : RoHS , ErP

- Applications
 - Industrial Control System
 - Networking Server System
 - Security Industry