



489.00 EUR

incl. 19% VAT, plus shipping

- INTEL® Bay Trail-M 2930 SoC Processor
 - Single Channel DDR3L 1333MHz SDRAM up to 4GB
 - Support CPU Smart FAN
 - Giga LAN Port * 2
 - Support 100M LAN Port * 4 (DC52.5V-1.94A-102W)
 - Support Watch dog Technology
 - Support AC 90~240V input
 - Applications : Industrial Control System, Networking Server System, Security Industry
- | | |
|---|--|
| <ul style="list-style-type: none"> • Product Dimension • Product Model • MB Model & Size • BIOS • CPU • Memory • Storage Space • Colors • Front I/O Port | <ul style="list-style-type: none"> • 264 (W) * 199.4 (D) * 38 (H) mm • JBC512F532(W)-2930-B • NF532P-2930 / 3.5" SBC • AMI UEFI • INTEL® Bay Trail-M 2930 SoC Processor • Single Channel DDR3L 1333MHz SDRAM up to 4GB • 2.5" SATA Device * 1 • Black • 4 PIN AC Input * 1 • AC ON-OFF * 1 • Power LED * 1 • Power SW * 1 • USB 2.0 * 2 |
|---|--|

- Rear I/O Port
 - USB3.0 * 1 , USB2.0 * 3
 - DVI-I * 1
 - Giga LAN Port * 2
 - Audio * 1 (Line out)
 - WiFi Port * 2 (JBC512F532W-2930-B only)
- POE Port
 - 100M LAN Port * 4 (DC52.5V-1.94A-102W)
 - Conforms to IEEE802.3, IEEE 802.3u, IEEE802.3af, IEEE802.3at
 - IEEE802.3x Flow control
 - Provides 4 PoE injector, per port DC52.5V-0.48A-25W
 - For Switch : IP178G
 - For PoE : MAX5980
- Power Source
 - 150W AC to DC OP Power inside
 - AC 90~240V input
- Accessory
 - AC Cable * 1
 - 4 Pin Terminal block con * 1
 - User Manual * 1
 - CD * 1
 - Screw Package * 1
- Packing
 - Net Weight : 3.6KG
 - Gross Weight : 4.5KG
 - Color Box Dimension : 406 (W) x 148 (D) x 359 (H) mm
- Temperature
 - Operating within 0~50 centigrade
 - Storage within -10-70 centigrade
- Certification
 - EMC : CE , FCC
 - Safety : RoHS , ErP
- Applications
 - Industrial Control System
 - Networking Server System
 - Security Industry