



- Watchdog
- Prepared for GPS, WLAN, GSM/GPRS with ext. antennas
- 4x DI / 4x DO with Relay 12V / 100mA
- Vibration/shock tested

For FleetPC-7-B we offer an [direct connector cable for our TFT-displays](#).

Dimensions / Weight	229mm W x 161mm D x 65mm H, 1.4kg
CPU	Intel Dual Core i3-4010U 1.70 GHz
RAM	1x SO-DDR-3L RAM (up to 8GB)
Graphics	Intel HD Graphics
Expansion	- 4x Mini-PCle
OS Support	Windows 7, Windows 8.1, Windows 10, Linux
Vibration & Shock	MIL-STD-810F
Operating temperature	-40~70°C (with SSD)
Certification	CE, FCC, eMark
I/O	<ul style="list-style-type: none"> <li>- 2x Gigabit LAN (Intel i210-AT) [PoE 802.3af]</li> <li>- 1x Gigabit LAN (Intel i218LM) [vPro]</li> <li>- 4x RS232 (2x with 232/422/485)</li> <li>- 2x USB3.0</li> <li>- 1x USB2.0</li> <li>- GPIO port (4in, 4out, with Relay 12V/100mA)</li> <li>- Mic-In, SPK Out</li> <li>- 1x DVI-I (for DVI-D and VGA), 1x HDMI</li> <li>- 4x SMA Antenna hole (for eg. GPS, GSM/GPRS/3G, WLAN, Bluetooth)</li> </ul>
Drive bays	1 x 2.5" SATA HDD/SSD drive bay, 1x SATA DOM
Power supply	9~36V DC PSU included <ul style="list-style-type: none"> <li>- Power off Delay Time Setting by Software, Default 5min</li> <li>- <a href="#">Backup Battery Kit (optional)</a></li> </ul>
Scope of Supply	- FleetPC-7-B PC mit Intel Core i3-4010U (2x1.7Ghz), Halterung