



489.00 EUR

incl. 19% VAT, plus shipping

- INTEL® Bay Trail-D 1900 SoC Processor
- Support 4GB DRAM on board
- Support CPU Smart FAN
- Giga LAN Port * 2
- Support 10/100M/1000M Base-TX RJ45 Ports * 4
- Support Watch dog Technology
- Support AC 90~240V input
- Applications : Industrial Control System, Networking Server System, Security Industry
- Product Dimension
 - 264 (W) * 199.4 (D) * 38 (H) mm
- Product Model
 - JBC512F3DG(W)-1900-B
- MB Model & Size
 - NF3DP-1900 / 3.5" SBC
- BIOS
 - AMI UEFI
- CPU
 - INTEL® Bay Trail-D 1900 SoC Processor
- Memory
 - 4GB DRAM on board
- Storage Space
 - 2.5" SATA Device * 1
- Colors
 - Black
- Front I/O Port
 - 4 PIN AC Input * 1
 - AC ON-OFF * 1
 - Power LED * 1
 - Power SW * 1
 - USB 2.0 * 2

- Rear I/O Port
 - USB3.0 * 1 , USB2.0 * 3
 - DVI-I * 1
 - Giga LAN Port * 2
 - Audio * 1 (Line out)
 - WiFi Port * 2 (JBC512F3DGW-1900-B only)

- POE Port
 - 10/100M/1000M Base-TX RJ45 Ports * 4
 - Conforms to IEEE802.3af, IEEE802.3at
 - IEEE802.3x Flow control
 - IEEE 802.3x full-duplex flow control , per port up to 23W
 - For Switch : Marvell 88E6176
 - For PoE : MAX5980

- Power Source
 - 150W AC to DC OP Power inside
 - AC 90~240V input

- Accessory
 - AC Cable * 1
 - 4 Pin Terminal block con * 1
 - User Manual * 1
 - CD * 1
 - Screw Package * 1

- Packing
 - Net Weight : 3.6KG
 - Gross Weight : 4.5KG
 - Color Box Dimension : 406 (W) x 148 (D) x 359 (H) mm

- Temperature
 - Operating within 0~50 centigrade
 - Storage within -10-70 centigrade

- Certification
 - EMC : CE , FCC
 - Safety : RoHS , ErP

- Applications
 - Industrial Control System
 - Networking Server System
 - Security Industry