



819.00 EUR

incl. 19% VAT, plus shipping

- M/B Model: NF9HG-2930
 - INTEL® Bay Trail-M/D/I Processor Processor
 - 2 * SO-DIMM slot (Max to 8GB)
 - 1 * full size Mini PCI-E slot for m-SATA Device
 - 1 x mini-PCle(Full Size), 1 x mSATA(Full Size),
 - 2 x PClex1
 - 2 * 2.5" SATA HDD
 - Application: Networking, POE, Surveillance
- | | |
|--|---|
| <ul style="list-style-type: none"> • Product Dimension • Product Model • MB Model & Size • BIOS • CPU • Memory • Storage • Expansion | <ul style="list-style-type: none"> • 430 (W) * 251 (D) * 43 (H) mm • JBC153F9HG-2930-B • JBC153F9HG-2930G2 • JBC153F9HG-2930G4 • JNF9HG-2930 / MINI-ITX • AMI 64Mb Flash ROM • INTEL® Bay Trail – M/D/I Processor (2930) • SO-DIMM DDR3L 1333/1066MHz * 2 (Max 8GB) • 2.5" SATA HDD * 2 • Full size Mini-PCIE * 2 (Support M-SATA*1) • SIM Card Slot * 1 • Support TPM (option) • 2 x PClex1 |
|--|---|

- FAN
 - Front I/O Port
 - Rear I/O Port
 - Power Source
 - Accessory
 - Packing
 - Temperature
 - Certification
 - Applications
- DC-12V / 4020 FAN * 3
 - Power LED * 1 , HDD LED * 1
 - COM * 2 , GPIO * 1
 - VGA * 1
 - USB 3.0 * 1 , USB 2.0 * 1
 - Giga LAN (Intel i211AT) * 4
 - Expansion 2 ports LAN PCI-E Card (JBC153F9HG-2930G2)
 - Expansion 4 ports LAN PCI-E Card (JBC153F9HG-2930G4)
 - AC input * 1
 - PW SW * 1
 - 1U 200W FLEX POWER
 - AC 90~240V input
 - AC Cable * 1 , Screw Package * 1
 - User Manual * 1 , CD * 1
 - Net Weight : 4.2KG
 - Gross Weight : 5KG
 - Color Box Dimension : 560 (W) x 400 (D) x 380 (H) mm
 - Operating within 0~60 centigrade
 - Storage within -10-70 centigrade
 - EMC : CE , FCC
 - Safety : RoHS , ErP
 - Networking
 - Surveillance