

1139.00 EUR

incl. 19% VAT, plus shipping



- INTEL® BayTrail--M N2930 SOC Chip
- Onboard INTEL® BayTrail-M N2930 1.83GHz Quad Cores CPU
- Onboard SAMSUNG 4G/1333MHz DDR3L Memory
- Support DirectX 11 3D Graphics Acceleration
- Support 1*Serial ATAll(3Gb/s) Devices
- Support Dual INTEL® Gigabit LAN
- Support CRT Output
- Equipped with 802.11 b/g/n WIFI card & External Antenna
- Support 3* COM ports (COM2/COM3 Support RS422/485)
- Support 2.5" SATA HDD
- Support 1*M-SATA Socket
- Support 1*Mini PCI-E Socket
- Support 3* USB2.0 Ports
- Support 1* USB3.0 Port
- Support 3G SIM Card
- Support slick design, IP65 Rating
- VESA mount(100mm X100mm &75mm x 75mm)

| | | |
|-------|---------------------|------------------------------|
| Panel | Panel Spec | AUO G170ETN01.0 |
| | Viewable Size Image | 17.0 inch With LED Backlight |
| | Active Area | 337.920(H) x 270.336(V) |
| | Resolution | 1280 x 1024 @60Hz |
| | Display Color | 16.7M |

| | | |
|-------|--------------------|--------------------------------------|
| | Pixel Pitch | 0.264 x 0.264 mm |
| | Aspect Ratio | 4:3 |
| | Contrast Ratio | 1000:1 |
| | Max Brightness | 350 cd/m ² |
| | Viewing Angle(H/V) | H170/V160 |
| | Response Time | 3.5ms |
| | Temperature Range | 0 ~ +50°C(Operating) |
| Touch | Touch panel style | 5 wires analog resistive |
| | Active Range | 337.00 x 269.50mm ±0.2mm |
| | Temperature Range | -10 ~ +60°C(Operating) |
| | Transparency | 80 ±3% |
| | Surface Hardness | ≥ 3H (ASTM D3363, pressure 750g/45°) |
| | Operating Force | ≦ 80g |
| | Knock test | 10,000,000 times keystrokes |