



CARTFT.COM
Shop for mobile
PC- and GPS-Solutions

Jetway HPC-170SRC-ITQ170 Panel-PC (17" 1280x1024 5W Touchscreen, Intel Q170 LGA1151, 4GB RAM)

[<http://www.cartft.com/catalog/il/2242>]



1194.00 EUR

incl. 19% VAT, plus shipping

- 17.0" 350 nits high brightness SVGA TFT LCD with LED backlight
- Onboard Intel® Q170 Express Chipset
- Supports Intel LGA 1151 Socket Core™ i3, i5, i7 & Pentium Processors
- 2* Dual Channel DDR4 2133MHz up to 32GB
- Support Dual Intel® Gigabit LAN
- Support 4 * COM ports (COM1/3 Support RS232/422/485)
- Support 6*USB3.0 Ports
- Support 2.5" SATA HDD, 1 * M-SATA connector
- Support 1*PCI or PCI-Ex16 , 2 * Mini PCI-E
- Support Camera for remote monitoring
- Plastic and IP65-rated front bezel

Display

Front Bezel

- IP65, NEMA 4 rugged protection, metal front bezel

| | |
|----------------------------------|----------------------------|
| Display Type | - 17.0" With LED Backlight |
| Brightness (cd/m ²) | - 350 nits |
| Display Color | - 262K |
| Resolution | - 1280 x1024 @ 60Hz |
| Viewing Angle (H/V) | - 170°/160° |
| Pixel Pitch | - 0.264 x 0.264 mm |
| Aspect Ratio | - 4:3 |
| Contrast Ratio | - 1000:1 |
| Response Time | - 3.5 ms |

Touch screen

| | |
|------------------|---|
| Type | - 5 wires analog resistive type |
| Active Range | - 337.00 x 269.50mm ±0.2mm |
| Transparency | - 80 ±3% |
| Surface Hardness | - \geq 3H (ASTM D3363, pressure 750g/45°) |
| Operating Force | - \leq 80g |
| Knock test | - 10,000,000 times keystrokes |

Main System

| | |
|-----|-------------------------|
| CPU | - Intel® LGA1151 Socket |
| RAM | - DDR4 2133MHz Max 32GB |

| | |
|----------------------------|--|
| BIOS | - 128MB SPI Flash ROM |
| Storage | - 1 * 2.5" SATA HDD - 1 * M-SATA connector |
| Watchdog Timer | - 255 levels, 0~255 sec. |
| OS Support | - Windows 7 / 8.1 / 10 / Linux |
| I/O Connector | |
| I/O Ports and Switches | - 6 * USB3.0 - 2 * RS232 - 2 * RS232/422/485 - 1 * DVD-D,HDMI,DP - 2 * LAN (Intel® I211AT+I219LM Gigabit LAN) - 1 * 110~240V AC input - 1 * Audio Jack - 1 * Expansion card - 1 * Power button |
| Expansion Interface | |
| Expansion | - 2 * PCI-E mini card for WIFI or 4G/3G |
| Power | |
| Power Input | - AC version: 100~240V AC |
| Dimensions | |
| Case Dimensions | - 421*354*91mm |

| | |
|-----------------------|---|
| Packing Dimensions | <ul style="list-style-type: none"> - Net Weight: 7.62KG - Gross Weight: 9.35KG - Color Box dimension: 476*160*460mm |
| Certifications | |
| Certifications | <ul style="list-style-type: none"> - CE, FCC , IP65 (Front) |
| Environment | |
| Temperature | <ul style="list-style-type: none"> - Operating: -10°C ~ 60°C (with W.T. DRAM/HDD in airflow condition) - Operating: -10°C ~ 60°C (with W.T. DRAM/HDD) |
| | <ul style="list-style-type: none"> - Storage: -20°C ~ 65°C |
| Shock | <ul style="list-style-type: none"> - Operating: 15G , 11ms duration |
| Vibration | <ul style="list-style-type: none"> - Operating: 5~500Hz/1 Grms |
| Warranty | |
| Warranty | <ul style="list-style-type: none"> - The warranty of 2 years, panel the warranty of 1 year |