




829.95 EUR

incl. 19% VAT, plus shipping

- **Dual LAN !**
- **4x COM !**
- **8-24V DC input !**
- **Mini-PCI Express !**



**Support:**  [Specifications](#)

Scope of supply : Mainboard with CPU and heatsink.

- Intel Kaby Lake ULV Core i3/i5/i7 Processor
- Intel HD graphics and DirectX 12 support
- Dual channel DDR4 with two connectors for MAX. 32GB memory
- Support triple display for HDMI, DisplayPort and LVDS / eDP
- Features high speed Dual Gigabit Ethernet
- Features 1 SATA 6Gb/s
- Four SuperSpeed USB3.0 ports support
- Three RS232 + One RS232/422/485 ports
- One PCI Express Mini Card connector for expansion
- One M.2 2232 (E key) for expansion
- 8 V to 24 V wide-range voltage input

**Item**

**Spec**

Form Factor

3.5" single board computer, 102mm x 147mm (4" x 5.8")

Processor Chipset	Intel Kaby Lake-U i5-7300U with integrated graphics (Compatible with 3955U/i3-6100U/i5-6300U/i7-6600U and 3965U/ i3-7100U/i7-7600U)	
Main Memory	<ul style="list-style-type: none"> <li>• 2 x 260-pin DDR4 SO-DIMM slot</li> <li>• Max capacity up to 32GB</li> </ul>	
Audio Controller	Realtek ALC283	
Expansion Capability	<ul style="list-style-type: none"> <li>• M.2 2230 (E Key) with (PCIex1/USB2.0)</li> <li>• Mini PCIe (full length, USB/PCIe/SATA)</li> </ul>	1 1
External I/O	<ul style="list-style-type: none"> <li>• HDMI-out</li> <li>• Display port</li> <li>• USB3.0</li> <li>• RJ-45</li> <li>• Audio combo jack (Mic-in and Line-out)</li> </ul>	1 1 4 2 1
Internal I/O	<ul style="list-style-type: none"> <li>• LVDS/eDP</li> <li>• 7-pin SATA connector</li> <li>• 4-pin SATA power</li> <li>• USB2.0</li> <li>• RS-232</li> <li>• RS-232/422/485</li> <li>• Audio header supporting system stereo speaker or buzzer</li> <li>• MiAPI header</li> <li>• Chassis front panel header</li> </ul>	1 1 1 2 3 1 1 1 1
SIO Controller	NCT6104D	
LAN Support	<ul style="list-style-type: none"> <li>• 1 x I219LM, 1 x I211AT</li> </ul>	
BIOS	AMI UEFI	
Hardware Management	<ul style="list-style-type: none"> <li>• Nuvoton NCT6104D based subsystem, including:</li> <li>• Voltage sense to detect out of range power supply voltages</li> <li>• Thermal sense to detect out of range thermal values</li> </ul>	
Environment	<ul style="list-style-type: none"> <li>• Operating Temperature: 0°C ~ 60°C (32°F ~ 140°F)</li> <li>• Storage Temperature: -20°C ~ 80°C (-4°F ~ 140°F)</li> <li>• Relative Humidity: 95% @60°C non-condensing</li> </ul>	

## Certification

- CE
- FCC