


999.00 EUR

incl. 19% VAT, plus shipping



- Intel® Apollo Lake Series Processor
- Support 1 \* DDR3L SO-DIMM, up to 8GB (option) to secure customers data
- Support 2 \* Display Port & 1 \* eDP port
- Support Triple Display, max 4K@60Hz resolution
- 1 \* External RS232(RJ45 Type) & 5 \* Internal COM (COM 2 support RS232/422/485)
- 4 \* External USB3.0 & 2 \* Internal USB2.0
- 1 \* Full size Mini PCIe , 1 \* M.2 SATA interface
- SIM card holder & micro SD socket

The JETWAY NF631 series are 3.5" form factor board adopts the Intel® Apollo Lake N3350/N4200 SoC Processor. The board supports one 204-pins SO-DIMM DDR3L memory, up to 8GB. Featuring the integrated Intel® i211AT Gigabit Ethernet controller for Gigabit Ethernet connection, the NF631 offers two 10/100/1000Base-TX Ethernet devices for network transmission. One SATAIII (6Gb/s) interface, micro SD socket and one M.2 (M-key, 2242) interface offer ample storage options. One Mini PCIe interface and SIM card holder are for 3G/LTE connection. Four USB3.0 ports, two USB2.0 ports and six COM ports provide versatile expansion. The NF631 offers two DP and one eDP ports which can support triple independent output and display up to 4Kx2K@60Hz resolution. Because of these features, NF631 is suitable for digital signage or kiosk or industry use.

## Form Factor

Dimensions

– 3.5" (5.8-in \* 4.0-in, 148 \* 102mm)

## Processor System

CPU	– Intel® Apollo Lake series Processor
Core Number	– (by CPU)
Max Speed	– (by CPU)
L2 Cache	– (by CPU)
Chipset	– SoC
BIOS	– AMI Flash ROM

## Expansion Slot

Mini-PCIe	– 1 (full size)
mSATA	– 0
PCIe	– 0
M.2	– 1 (M key 2242)
SIM Card Holder	– 1

## Memory

Technology	– DDR3L 1867MHz SDRAM
Max.	– 8GB
Socket	– 1 * SO-DIMM

## Graphics

Controller	– Intel® HD Graphics
VRAM	– Shared Memory
VGA	– 0
LVDS	– 0
eDP 1.3	– 1 (Max. Resolution : 4096 * 2160@60Hz)
HDMI 1.4	– 0
DisplayPort	– 2 (Max. Resolution : 4096*2160@60Hz)
MultiDisplay	– Triple Display

## Ethernet

Ethernet	– 10/100/1000 Mbps
Controller	– Intel i211AT Gigabit LAN
Connector	– 2 * RJ 45

## Audio

CODEC	– HD Audio : Realtek ALC662
Channel	– 2 Channel (combo Line Out + Mic)

## SATA

Max Data Transfer Rate	– 1 * SATAIII (6.0Gb/s)
------------------------	-------------------------

## Rear I/O

VGA	- 0
DisplayPort	- 2
Ethernet	- 2
USB	- 4 * USB 3.0
Audio	- 1 (Line out + MIC combo)
Serial / Parallel	- 1 (RJ-45 type) / 0
PS2	- 0
DC-input	- 1

## Internal Connector

USB	- 2 * USB 2.0
PS/2	- 1
LVDS / inverter	- 0
eDP	- 1
Serial	- 5 (4 * RS232 , COM 2 support RS232/422/485)
SATA	- 1 * SATAIII (6.0Gb/s)
mPCIe	- 1 (full size)
mSATA	- 0
M.2	- 1 (M key-2242)

GPIO	– 1 (8 bit)
Chassis intrusion	– 1
Audio Header	– 1
SMBUS/ I2C	– 1
AT mode	– 1
TPM Header	– 0
Others	– 1 * micro SD card slot

## Watchdog Timer

Output	– From Super I/O to drag RESETCON#
Interval	– 256 segments (10sec ~ 255min)

## Power Requirements

Input PWR	– 12V DC-in
Power On	AT/ATX Supported – AT : Directly PWR on as Power input ready – ATX: Press Button to PWR on after Power input ready

## Certifications

Certifications	– CE, FCC, RoHS, REACH
----------------	------------------------

## Environment

Temperature	– Operating: 0°C – 60°C
-------------	-------------------------

– Storage: -20°C – 85°C

## Warranty

Warranty

– 2 Years Limited Warranty