


259.00 EUR

incl. 19% VAT, plus shipping



- Intel® H81 Express Chipset
- Support INTEL® 4th Gen core processors family
- Support DDR3 /DDR3L 1600/1333 Max 16GB
- 2\* GbE, 4\* USB3.0, 7\* USB2.0, 6\* COM (COM 1/2 support RS232/422/485, COM 1/2/3/4 support 5V/12V)
- Support SIM Card Socket
- Support 1\* CRT Port, 2\* HDMI
- ATX Form Factor (305\* 240mm)

## Form Factor

Dimensions	– ATX (305 * 240mm)
------------	---------------------

## Processor System

CPU	– Intel® LGA 1150 Socket Core i7/i5/i3/Pentium Processor
Core Number	– (by CPU)
Max Speed	– (by CPU)

L2 Cache	– (by CPU)
Chipset	– Intel H81 Express chipset
BIOS	– AMI 32Mb Flash ROM
<b>Expansion Slot</b>	
PCI	– 5
Mini-PCIe	– 1 (Full size)
mSATA	– 1 (full size ,Co-lay SATA4)
PCIe	– 2 (x16 + x1)
TPM Header	– 1
SIM Card Holder	– 1
<b>Memory</b>	
Technology	– DDR3L 1600/1333MHz
Max.	– 16GB
Socket	– 2* DIMM Socket
<b>Graphics</b>	
Controller	– Intel® HD Graphics
VRAM	– Shared Memory
VGA	– 1

LVDS	- 0
eDP	- 0
HDMI 1.4	- 2
Display Port	- 0
<b>Ethernet</b>	
Ethernet	- 10/100/1000 Mbps
Controller	- 2 * Realtek RTL8111G Gigabit LAN
Connector	- 2 * RJ 45
<b>Audio</b>	
CODEC	- HD Audio : Realtek ALC662
Channel	- FP_AUDIO, 3W Amplifier Speaker out
<b>SATA</b>	
Max Data Transfer Rate	- 2 * SATA2.0 (3.0Gb/s) + 2* SATA3.0(6.0Gb/s)
<b>Rear I/O</b>	
VGA	- 1
DVI-D	- 0
HDMI	- 2
Display Port	- 0

Ethernet	- 2
USB	- 4* USB 3.0 + 2* USB2.0
Audio	- 1 (3JACK)
Serial / Parallel	- 2 (RS232/422/485)
PS2	- 1
<b>Internal Connector</b>	
USB	- 5 * USB 2.0
PS/2	- 0
LVDS / inverter	- 0
eDP	- 0
VGA	- 0
Serial	- 4 ( COM 3/4 Support 5V/12V)
SATA	- 2* SATA2.0 + 2* SATA3.0
mPCIe	- 1 (Full size)
Parallel	- 1
m-SATA	- 1 (full size, Co-lay SATA6)
GPIO 8-bit	- 1 (4 * IN +4 * OUT)
Chassis intrusion	- 1

Audio Header	- 0
SMBUS/ I2C	- 1
AT mode	- 1
TPM Header	- 1
Others	- 0

## Watchdog Timer

Output	- From Super I/O to drag RESETCON#
Interval	- 256 segments, 0,1,2...255sec/min

## Power Requirements

Input PWR	- 4 Pin / 24 Pin ATX PWR Connector
Power On	<p>AT/ATX Supported</p> <ul style="list-style-type: none"> <li>- AT : Directly PWR on as Power input ready</li> <li>- ATX: Press Button to PWR on after Power input ready</li> </ul>

## Certifications

Certifications	- CE, FCC, RoHS, REACH
----------------	------------------------

## Environment

Temperature	- Operating: -10°C – 60°C
	- Storage: -20°C – 85°C

## Warranty

Warranty

– 2 Years Limited Warranty