



849.00 EUR

incl. 19% VAT, plus shipping

- 10.4" 400 nits high brightness TFT LCD with LED backlight
- 5 Wire Resistive Touch/Anti-Reflection Protection Glass
- Streamlined enclosure for highly efficient heat dissipation Enclosed in robust aluminum casing
- Strong solid aluminum frame design and Fanless cooling system
- Support Open frameless design
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- Lockable USB device bracket supported
- IO Ports designed for easy connection
- 9-28V DC-input Support, with EOS, OVP design

Jetway HPC104GR-HD1900B heavy-duty Fanless Panel PC offers complete robust solution for harsh industrial environments, such as cloud computing, IoT solution, transportation, heavy-vehicles, intelligent building, oil pipe monitoring systems, environmental monitoring, steel refineries, machine control and factory automation.

Jetway HPC104GR-HD1900B heavy-duty Fanless Panel PC is designed with 5-wires resistive touch screen for 4:3 size panel. High brightness TFT LCD panel with LED backlight are equipped with all models. Cable-free design is easy for the HDD and memory installation. Streamlined enclosure with strong solid aluminum frame design, it provides good heat dissipation and achieve fanless cooling system.

Jetway HPC104GR-HD1900B heavy-duty Panel PC is also designed for open frame application. Heavy-duty Panel PC is designed mounting clips for easy Wall mount, Panel Mount, VESA Mount installation.

It is a true flat flat with easy clean design, front bezel meets IP65-rated & NEMA 4 protection. Welcome to use Jetway heavy-duty Panel PC.

Display	
Front Bezel	- NEMA 4 rugged protection, metal front bezel
Display Type	- 10.4" With LED Backlight
Brightness (cd/m ²)	- 400 nits
Display Color	- 262K
Resolution	- 800 x 600 @ 60Hz
Viewing Angle (H/V)	- 130°/140°
Aspect Ratio	- 4:3
Contrast Ratio	- 400:1
Response Time	- 25 ms
Touch Screen	
Type	- 5 wires analog resistive type
Active Range	- 211.58 x 158.75mm ±0.2mm
Operating Force	- ≦ 80g
Transparency	- 80 ±3%
Surface Hardness	- ≧3H (ASTM D3363, pressure 750g/45°)

Knock test - 10,000,000 times keystrokes/span>

CASE

Panel Material - Aluminum

Case Material - Iron

Color - Silver + white

Coating Requirement - Spray Paint

Main System

CPU - Intel® Bay Trail-D J1900 2.0GHz/QC

RAM - 4G 1333MHz DDR3L SAMSUNG DRAM

BIOS - 64MB SPI Flash ROM

Storage - 1* 2.5" SATA bay
- 1* M.2 connector (2242/2260/2280)

Watchdog Timer - 256 levels, 0~255 sec.

OS Support - Windows 7 / 8.1 / 10 / Linux (Option)

I/O Connector

I/O Ports and Switches

- 2* USB3.0
- 2* USB2.0
- 2* USB2.0 (Front)
- 2* RS232/422/485
- 1* CRT
- 1* 8bit GPIO
- 2* LAN (Intel® I211AT Gigabit LAN)
- 1* Locking Jack 9~28V DC input
- 1* Power button

Expansion Interface

Expansion

- 1 * PCI-E mini card for WIFI or 3G/4G
- 1 * SIM card holder for 3G/4G

Power

Power Input

- Supports 9-28V DC Power in with over current protection fuse
- Provides 100~240V AC-DC 12V, 60W power adapter

Power Consumption

- 25W

Dimension

Case Dimensions

- 290.0*226.0*63.0mm

Certifications

Certifications

- CE, FCC

Environment

Temperature

- Operating Temperature: -10 ~ 60° C (with W.T. DRAM/HDD in airflow condition)
- Operating Temperature: -10 ~ 60° C (with W.T. DRAM/HDD)
- Storage Temperature: -20 ~ 85° C

Shock

- Operating: 15G , 11ms duration

Vibration

- Operating: 5~500Hz/1 Grms

Warranty

Warranty

- 2 Years Limited Warranty(Panel and Touch is only Warranty 1 Year)