



229.00 EUR

incl. 19% VAT, plus shipping

Support:  [Jetway ARM Overview](#)

- Support Rockchip RK3288 Quad-core processor
- On-board 2GB DDR3 DRAM and 8GB flash ROM
- Supports HDMI
- Supports 1* Mini PCIe, 1 * TF card socket
- Supports 6* USB2.0, 1 * OTG, 4* COMs
- 3.5" Form Factor

Form Factor

Dimensions

-3.5" SBC (102 * 146mm)

Processor System

CPU

- Rock chip® ARM Cortex A17 RK3288 1.8GHz

Core Number

- Quad-core

Max Speed

- 1.8G

L2 Cache

- 0

Chipset	– Rock chip® ARM Cortex A17 RK3288 SoC
BIOS	– 0
PMU	– Rock chip® RK808-B
Expansion Slot	
PCI	– 0
Mini-PCIe	– 1 (full size , by USB interface)
SIM card holder	– 1
Technology	– Onboard DDR3L 1333MHz 2GB
Max.	– 4GB
Socket	–
Flash Rom	– 8GB (Max 32GB)
Graphics	
Controller	– (by CPU)
VRAM	– Shared Memory
VGA	– 0
LVDS	– 1 * 24 bit Dual Channel connector
eDP	– 1 * eDP support up to 3840*2160@60Hz
HDMI	– 1 (2.0)

DVI-D	- 0
MultiDisplay	- Dual Display
Ethernet	- 10/100/1000 Mbps
Controller	- 1 * Realtek RTL8211E-VB Gigabit LAN
Connector	- 1 * RJ 45
Audio	
CODEC	- HD Audio : ES8316
Channel	- 2 Channel
Special Features	
WIFI	- 802.11 b/g/n,2.4G
WIFI Chip	- RTL8723BS
Bluetooth	- BT-V4.0 BLE
3G	- WCDMA, EVDO,CDMA,GSM (Option)
LTE	- LTE-TDD/LTE-FDD/TD-SCDMA/EDGE/GPRS/GSM (Option)
OS	- Android 5.1
VGA	- 0
DVI-D	- 0
Display Port	- 0

Ethernet	- 1
Audio	- 1 (Line-Out, MIC)
Serial	- 0
SIM Socket	- 1
TF Card Socket	- 1
LVDS / inverter	- 1 (24 bit)
USB	- 4 (4 * USB 2.0)
Others	- 1 * I2C
SATA	- 0
Interval	- 256 segments, 0,1,2...255sec/min
Power Requirements	
Input PWR	- 12V DC-in (PWR Con)
Power On	AT/ATX Supported - AT : Directly PWR on as Power input ready - ATX: Press Button to PWR on after Power input ready
Certifications	
Certifications	- CE, FCC, RoHS, REACH
Warranty	
Warranty	- 2 Years Limited Warranty

Temperature

– Operating: 0°C ~ 45°C

– Storage: -20°C ~ 65°C

Packing

– Net Weight:

- Gross Weight:

- Color Box dimension: