



999.00 EUR

incl. 19% VAT, plus shipping

- Intel® Apollo Lake N3350/N4200 Processor
- 1 * SO-DIMM Dual CH DDR3L up to 8GB
- 2 * USB3.0, 6 * RJ45, 1 * RS232(RJ45 TYPE)
- M/B Form Factor : Mini ITX (170x170mm)
- 1U FLEX POWER_200W

MB Model	- JNF692G6-335 / JNF692G6-420 (Mini-ITX) - JNF692G6-335B1 / JNF692G6-420B1 (Mini-ITX/1 pair support Bypass LAN)			
Part No	- HBJC153F692-335B - HBJC153F692-420B			
	Bypass LAN	Expansion 4 ports LAN PCI-E Card	Bypass LAN+ Expansion 4 ports LAN PCI-E Card	2 Paris of Bypass LAN
	- HBJC153F692B-335B	- HBJC153F692-33G4	- HBJC153F692B-33G4	- HBJC153F692-33B4
	- HBJC153F692B-420B	- HBJC153F692-42G4	- HBJC153F692B-42G4	- HBJC153F692-42B4
BIOS	- AMI 128MB SMT Flash ROM			
CPU/Chipset	- INTEL® Apollo Lake N3350/N4200 Processor			

Memory	- 1 * SO-DIMM slots DDR3L-1866MHz up to 8GB
Storage	- 1 * 2.5" SATA3 6Gb/s internal drive bay - 1 * Full-size mSATA/mini-PCI Express shared slot
Expansion	- 1 * Full size Mini-PCIE - 1 * SIM Card Slot
Network	- 6 * Intel i211AT Gigabit LAN - 1 * Full-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model)
Rear Panel I/O	- 1 * Power SWITCH - AC INPUT / 1U FLEX 200W Power build in
Front Panel I/O	- 6 * RJ45 - 2 * USB3.0 - 1 * RS232 (RJ45 TYPE) - 1 * PW LED, 1 * Alarm LED - 1 * HDMI (Not assembled when shipped, wire placed in the parts box) - 1 * GPIO (Not assembled when shipped, wire placed in the parts box) - 2 * COM (optional- RS232/422/485) Expansion 4 ports LAN PCI-E Card: HBJC153F692-33(42)G4 Expansion 2 pairs of Bypass LAN PCI-E Card: HBJC153F692-33(42)B4
Power Source	- 1U FLEX 200W Power build in - AC 90~240V input
Compliance	- CE, FCC, RoHS
Temperature	- Operating Temperature: 0 ~ 40° C - Storage Temperature: -10 ~ 70° C
Dimensions	- 430 (W) x 252 (D) x 44 (H) mm
Packing	- Net Weight: 4.2KG - Gross Weight: 5KG - Color Box dimension: 560 (W) * 400 (D) * 380 (H) mm

OS Support

- Windows 10, Linux

Warranty

- 2 Year limited warranty