



269.00 EUR

incl. 19% VAT, plus shipping

Support:  [Jetway ARM Overview](#)

- Rockchip® ARM Cortex A17 RK3288 Quad-core 1.8GHz
- Onboard 1333 /2GB DDR3L DRAM Max. 4GB
- Onboard 8G Flash ROM Max 32GB
- Support 1* Realtek® RTL8211E-VB Gigabit LAN
- 1* Realtek® RTL8723BS 802.11 b/g/n
- Support 1* Micro SD Socket (Max 64G)
- 1* USB2.0, 1* OTG, 1* RS232, 1* HDMI
- 12V DC-in

| | |
|-------------|--|
| MB Model | - JARMB3288W-2N (3.5" SBC) |
| Part No | - HBJC920R3288-2N |
| CPU/Chipset | - Rockchip® ARM Cortex A17 RK3288 1.8GHz Quad core - Rockchip® RK808-B |
| Memory | - 2GB/1333MHz DDR3L (Max 4GB) |
| Storage | - 8GB Flash (Max 32GB) |
| Network | - 1 * REALTEK RTL8211E-VB Gigabit LAN - On board 802.11 a/b/g/n/ac,2.4G - On board BT-V4.0 BLE |

| | |
|-----------------|---|
| Rear Panel I/O | <ul style="list-style-type: none"> - 1 * RJ45 - 1 * HDMI - 1 * Audio Jack - 1 * USB2.0 - 1 * OTG (Option USB2.0) - 1 * RS485 - 1 * Micro SD Socket - 1 * Power button - 1 * SIM Card Socket - 12V DC-Jack |
| Front Panel I/O | <ul style="list-style-type: none"> - 2 * Antenna hole |
| Power Source | <ul style="list-style-type: none"> - DC 12V-5.0A - AC 90~240V input |
| Compliance | <ul style="list-style-type: none"> - RoHS, ErP Ready |
| Safety | <ul style="list-style-type: none"> - Vibration test: N.C - Shock test: N.C |
| Temperature | <ul style="list-style-type: none"> - Operating Temperature: -10 ~ 60° C - Storage Temperature: -20 ~ 65° C |
| Dimensions | <ul style="list-style-type: none"> - 190 (W) x 115 (D) x 22 (H) mm |
| OS Support | <ul style="list-style-type: none"> - Android 5.1 |
| Warranty | <ul style="list-style-type: none"> - 2 Year limited warranty |