



639.00 EUR

incl. 19% VAT, plus shipping



- 7" 400 nits high brightness TFT LCD with LED backlight
- Alloy aluminum structure
- Camera Support superior low-light performance
- Camera Support high dynamic range imaging
- Support Face Recognition Living Body
- Face Recognition less than 0.5sec
- Support 30,000 face data base on board
- Stand support 15° up and down adjustment
- 12V DC-in

Display

Display Type	- 7" With LED Backlight
Brightness	- 400 cd/m ²

Display Color	- 16.7M
Resolution	- 800 x 1280 @ 60Hz
Viewing Angle (H/V)	- 170°/170°
Pixel Pitch	- 0.039 x 0.118 mm
Aspect Ratio	- 10:16
Contrast Ratio	- 800:1
Response Time	- 20 ms

Screen

Type	- Glass
------	---------

CASE

Panel Material	- Aluminum
Case Material	- Aluminum
Color	- Silver
Coating Requirement	- Oxidation treatment
Stand	- 15° up and down adjustment

Main System

CPU	- Rockchip® ARM Cortex A17 RK3288 Quad Cores 1.8GHz
RAM	- 2G 1333MHz DDR3L DRAM Max 4GB

Flash ROM	- 8GB Max 64GB
Storage	- 1* Micro SD Card Socket (INT)
Watchdog Timer	- 256 levels, 0~255 sec.
Fill Light	- 1 (Life time: > 30,000 Hours)
Camera	- 200W Full HD
OS Support	- Android 5.1
I/O Connector	
Cable	<ul style="list-style-type: none"> - 1* USB2.0 - 1* OTG - 1* RJ45(10/100/1000Mbps Ethernet) - 1* DC Jack - 1* Switch Control (3Pin Cable)
Power	
Power Input	<ul style="list-style-type: none"> - AC version: 100 ~ 240V AC-DC 60W power adapter or - DC version: 12VDC with over current protection fuse
Power Consumption	- 11.5W
Dimension	
Case Dimensions	- 221.0 * 120.0 * 36.0 mm
Certifications	
Certifications	- RoHS
Environment	

Temperature	- Operating Temperature: 0 ~ 60° C - Storage Temperature: -20 ~ 85° C
Shock	- Operating: 15G , 11ms duration
Vibration	- Operating: 5~500Hz/1 Grms
Warranty	
Warranty	- 1 Year Limited Warranty