



CARTFT.COM  
Shop for mobile  
PC- and GPS-Solutions

Jetway FPC-P101 POE Android Panel-PC (10.1" 1920x1200 Touchscreen, ARM 1.8Ghz, 2GB RAM, IP65 Front)

[<http://www.cartft.com/catalog/il/2614>]



999.00 EUR

incl. 19% VAT, plus shipping

- **Fanless !**
- **IP65 Front !**
- **POE !**
- **Android !**

Support:  [Specifications](#)

- 10.1" 300 nits TFT LCD with LED backlight
- Onboard DDR3L 1333 2GB DRAM
- Onboard 8G Flash ROM
- Strong solid aluminum frame design and Fanless cooling system
- Design for easy Wall mount, Panel Mount, VESA Mount installation
- A true Flat, easy-to-clean front surface with edge-to-edge design
- Front IP65 for protection against water and dust
- Front bezel meets IP65-rated protection
- Support PoE input
- Jetway also provides 13.3" and 15" Panel PC models, for other sizes please contact sales for more details

Display

Front Bezel	- IP65, NEMA 4 rugged protection, metal front bezel
Display Type	- 10.1" With LED Backlight
Brightness (cd/m <sup>2</sup> )	- 300 nits
Display Color	- 262K
Resolution	- 1920 x 1200 @ 60Hz
Viewing Angle (H/V)	- 140°/140°
Pixel Pitch	- 0.03775 x 0.03775 mm
Aspect Ratio	- 16:10
Contrast Ratio	- 500:1
Response Time	- 60 ms

**Touch Screen**

Type	- projected capacitive type
Active Range	- 257.10 x 159.66mm ±0.2mm
Transparency	- ≥87%
Operating Force	- ≤50g
Surface Hardness	- ≥6H (ASTM D3363, pressure 1N/45°)
Operating Temperature	- -10 ~ +60° C

**CASE**

Panel Material	- Aluminum
Case Material	- Iron
Color	- Black
Coating Requirement	- Spray Paint
<b>Main System</b>	
CPU	- Rock Chip® ARM Cortex A17 1.8GHz/QC
RAM	- 2G DDR3L
Flash ROM	- 8G Flash ROM
Watchdog Timer	- 256 levels, 0~255 sec.
Speaker	- 2* 2W/80hm
OS Support	- Android 5.1
<b>I/O Connector</b>	
I/O Ports and Switches	- 1* USB2.0 - 1* OTG - 1* PoE PD
<b>PoE</b>	
Regulatory Compliance	- IEEE802.3af (PoE)
Input Power	- 44~57V
Pass Through Data Rates	- 10/100/1000 Mbps

Power Consumption	- 8.5W
<b>Dimension</b>	
Case Dimensions	- 259.3*177.3*34.5mm
<b>Certifications</b>	
Certifications	- CE, FCC, IP65(Front)-Option
<b>Environment</b>	
Temperature	- Operating: -10 ~ 50° C - Storage: -20 ~ 60° C
Shock	- Operating: 15G , 11ms duration
Vibration	- Operating: 5~500Hz/1 Grms
<b>Warranty</b>	
Warranty	- 2 Years Limited Warranty (Panel and Touch are only 1 Year Warranty )