



469.00 EUR

incl. 19% VAT, plus shipping



- Intel® Skylake Celeron SoC Processor
- 1* 260-pin Dual-channel DDR4 2133MHz SODIMM Up to 16 GB
- 4* 10/100/1000 Base-TX Ethernet Ports
- 1* Full size Mini-SATA Socket (SATA + USB Signal)
- 2* Mini PCIe Slots (1* full size & 1* half size)
- 1* SIM card holder
- Supports on board TPM1.2/2.0 (option)
- 1* RS232 Console, 2* USB3.0, 2* USB2.0
- Supports Antenna up to 4

MB Model	- JNF731-XXXX / 3.5" SBC
Part No	- HBFDF731-3855-B (non-WIFI) / HBFDF731W-3855-B (WIFI) - HBFDF731-3955-B (non-WIFI) / HBFDF731W-3955-B (WIFI) - HBFDF731-3965-B (non-WIFI) / HBFDF731W-3965-B (WIFI)
Processor	- Intel® Skylake Celeron 3855U/3955U/3965U SoC Processor

Chipset	- SoC Integrated
Memory	- 1 * SO-DIMM DDR4-2133MHz up to 16GB
Storage	- 1 * 2.5" SATA3 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm) - 1 * full size mSATA
Network	- 1 * Intel® i219LM GbE & 3 * Intel® i211AT (Default on board)
Expansion slot	- 1 * half size Mini PCIe slot (for WiFi expansion) - 1 * full size Mini PCIe slot with 1 * SIM card holder)
Front Panel I/O	- 1 * Power button, 1 * Reset button - 1 * Power LED, 1 * HDD LED - 2 * USB2.0 - 4 * NIC LED - 1 * COM & 1 * GPIO (option)
Rear Panel I/O	- 4 * RJ45 (3 * i211AT + 1 * i219LM) - 2 * USB3.0 - 1 * HDMI (Reserve, Max. resolution:4096 x 2304@24Hz) - 1 * RS232 - 1 * DC-in jack
Other Features	- TPM1.2 or TPM2.0 (On board option) - 0~255 segments by software programmable
Power Source	- FSP DC Adapter / AC 90~240V input / DC12V-5A-60W / LV6
Safety	- CE, FCC, LVD, RoHS
Temperature	- Operating Temperature: 0 ~ 50° C - Storage Temperature: -10 ~ 70° C
Dimensions	- 193 (W) x 142.4 (D) x 62 (H) mm
Packing	- Net Weight: 2.2KG - Gross Weight: 3.2KG - Color Box dimension: 250 (W) * 118 (D) * 295 (H) mm
OS Support	- 32/64 bit versions of Windows 7, Windows 8.1, Windows 10, Linux
Warranty	- 2 Year limited warranty