



9999.00 EUR

incl. 19% VAT, plus shipping

- Intel® Skylake/Kabylake U Processor on board
- Support 2* SO-DIMM DDR4-2133, up to 32GB memory
- All-aluminium main body; Stainless base
- Support IP69K waterproof and dustproof level
- Flexible I/O for customized and mission-critical projects
- Stainless steel bottom cover with stainless steel screws for outdoor use without rust

MB Model	- JNF833 Series / 3.5" SBC
Part No	- HBFMF833-71-2L-B (non-WIFI) / HBFMF833W-71-2L-B (WIFI) - HBFMF833-71-2C-B (non-WIFI) / HBFMF833W-71-2C-B (WIFI) - HBFMF833-72-2L-B (non-WIFI) / HBFMF833W-72-2L-B (WIFI) - HBFMF833-72-2C-B (non-WIFI) / HBFMF833W-72-2C-B (WIFI)
BIOS	- AMI
CPU/ Chipset	- Intel® Skylake/Kabylake U Processor (TDP 15W) Notes: When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.
Memory	- 2 * SO-DIMM slots DDR4-2133MHz up to 32GB
Storage	- 1 * 2.5" SATA3 6Gb/s internal drive bay (only support 2.5" HDD with a hight ≤ 10mm) - 1 * Full-size mSATA/mini-PCI Express shared slot

Network	<ul style="list-style-type: none"> - 1 * Intel GbE (HBFMF833(W)-7X-2C-B) - 2 * Intel GbE (HBFMF833(W)-7X-2L-B) - 1 * Half-size mini-PCIE slot (802.11 b/g/n + BT 4.0 installed in WIFI model) 	
Rear Panel I/O	<ul style="list-style-type: none"> - HBFMF833(W)-7X-2C-B 	<ul style="list-style-type: none"> - HBFMF833(W)-7X-2L-B
	<ul style="list-style-type: none"> - 2 * USB2.0 - 1 * RJ45 - 2 * COM - 1 * HDMI - 2 * WIFI Antenna - 1 * DC-In 	<ul style="list-style-type: none"> - 1 * USB3.0 - 1 * USB2.0 - 2 * RJ45 - 1 * COM - 1 * HDMI - 2 * WIFI Antenna - 1 * DC-In
Front Panel I/O	<ul style="list-style-type: none"> - 1 * Power SW - 1 * Power LED 	
Power Source	<ul style="list-style-type: none"> - NF833 MB support DC9~24V input - FSP Adapter , AC 90~240V input , DC12V-5A-60W 	
Compliance	<ul style="list-style-type: none"> - CE, FCC, LVD, RoHS, ErP Ready 	
Waterproof	<ul style="list-style-type: none"> - IP69K 	
Safety	<ul style="list-style-type: none"> - ESD Test Report 	

Temperature	<ul style="list-style-type: none"> - Operating Temperature: -20 ~ 70° C (Under the condition of using mSATA or SSD) - Operating Temperature: 0 ~ 50° C (Under the condition of using 2.5" SATA HDD) (The test environment is closed and windless) - Storage Temperature: -10 ~ 70 °C - Humidity: 90%, non-condensing
Dimensions	- 250 (W) x 171 (D) x 54 (H) mm
Packing	<ul style="list-style-type: none"> - Net Weight: 4.5KG - Gross Weight: 5.5KG - Color Box dimension: 560 (W) * 400 (D) * 380 (H) mm
OS Support	<ul style="list-style-type: none"> - Skylake CPU support Win7, Win8, Win10. - Kabylake CPU only support Win10.
Warranty	- 2 Years limited warranty